

## Commercial Grade



### LEADS

Description	Rating	Cat. No.	OD	OH
2-Piece Ring Type with Leads: No. 18 AWG, 105°C Plastic; 9" Long, Stripped 3/4"	660W 250V	8101	1 3/4	1 3/8
Angle Pan with Leads: No. 18 AWG Type AF 150°C Plastic; 9" Long, Stripped 3/4"	660W 250V	18315	—	—
Removable Bracket with Leads	660W 250V	8052-1	1 3/8	1 7/16
Screw-Mount Pulse-Rated Lampholder with Leads for Open-Fixture Lamps; 18 AWG 200°C 600V SEW-2 (SF-2) wire; 9" Long, Stripped 1/2"	660W 600V 4KV Pulse Rated	70052-100	1 45/64	2 9/32

### Two-Piece Pull Chain

Description	Rating	Cat. No.	OD	OH
Ring Type; Screw Terminals; Gasket Furnished♦‡	250W 250V	9814	1 13/16	1 13/16

CSA Certified except where indicated by ♦ and NOM Certified except where indicated by ‡.

### TESTING AND CODE COMPLIANCE

- UL Listed (File #E-3810)
- CSA Certified (File #LR-1863)
- NOM Certified (File #057)

## Medium Base , Metal and Quartz Halogen Incandescent Lampholders

### Specifications and Features

- Cat. No. 3352 lampholder bodies have wireways
- Side-Mounted lampholders are white glazed porcelain with copper-alloy screwshell
- Recessed Single-Contact lampholders have porcelain body with nickel-plated steel housing
- Cat. No. 560 has a metal lamp-positioning clip (patent pending) that maintains lamp seating position
- Cat. No. 565 is designed for energy-efficient CDM lamps
- Cat. No. 570 twists in and is fully dimmable



### PHENOLIC KEYLESS FIXTURE

#### Medium Base Screw Terminals

Description	Rating	Cat. No.
Permanent Bracket. Terminal Screws Backed Out and Staked	660W 250V	3352-1
Same as 3352-1, with Shorter Bracket	660W 250V	3352-F
Removable Hickey. Terminal Screws Backed Out and Staked	660W 250V	3352-8

Hickeys and brackets are available in various types and sizes. Consult a Leviton representative for more information.

### PORCELAIN KEYLESS, SIDE-MOUNTED

#### Medium Base Screw Terminals

Description	Rating	Cat. No.
Single Lampholder w/Side Outlet Bushing — 1/8 IPS	660W 250V	10091
Twin Lampholder w/Bushed Flange — 1/8 IPS	660W 250V	4010
Twin Lampholder w/Single Outlet Bushing — 1/8 IPS	660W 250V	4005
Same as 4005 with 3/8 IPS Bushing	660W 250V	4006

All bushings are tapped and have set screw.

