Product data sheet
Characteristics

H60XFA
SWITCH NONFUSIBLE HD 600V 60A 3P NEMA7,9

Main

Commercial Status	Commercialised
Product	Single Throw Safety Switch
Current Rating	60 A
Certifications	CSA UL listed
Enclosure Rating	NEMA 7/9 cast aluminium
Factory Installed Neutral	None
Disconnect Type	Non-fusible disconnect
Short Circuit Current Rating	10 kA
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Screw-clamp terminals
Duty Rating	Heavy duty
Voltage Rating	250 V DC 600 V AC
Wire Size	14...6 AWG copper

RoHS compliance

RoHS EUR status	Will be compliant
RoHS EUR conformity date(YYWW)	3Q2014

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.