

### Wiha Multi-Bit Screwdrivers

*Six Tools in One!*

Insulated Bit Holder



Tested to 10,000 Volts Insulation meets EN/IEC 60900

**WH380 Sets Multi-Bit Screwdriver Sets** with Wiha Powerhandle, cellulose-acetate, impact resistant. Snap-lock rotatable cap.

Chambered bit holder equipped with transparent selector and 6 bits. 1/4" Bit holder, stainless steel. Shaft chrome-vanadium-molybdenum steel, hardened, chrome-plated. Packaged in clear blister package. Blade Length = 120mm (4.7") Overall Length = 230mm (9")

**WH38006 Slotted/Phillips Multi-Bit Screwdriver**

With Wiha Powerhandle and insulated shaft.

Set includes the following 1/4" bits:

↓ Slotted Sizes: 5.5, 6.5mm lbs.

⊕ Phillips Sizes: 0, 1, 2, 3 .39

**WH38007 Slotted/Phillips/Square Multi-Bit Screwdriver**

With Wiha Powerhandle and insulated shaft.

Set includes the following 1/4" bits:

↓ Slotted Sizes: 6.5, 8.0mm lbs.

⊕ Phillips Sizes: 1, 2 .41

⊖ Square Sizes: 1, 2

**WH38025 Magnetic Bit Holder, 1/4"** Wiha Powerhandle and insulated shaft. Holder only can hold up to 6 bits.

↔ lbs. .26

### Wiha Insulated TorqueControl Tools

Includes Certificate



⚡ 1000Volt

Includes *SlimLine* blade holder

**WH287 Insulated TorqueVario-S, With Window Scale Insulation**

⚡ up to 1000 Volt. EN/IEC 60900 EN ISO 6798, BS EN 26789, ASME B107.14M & CSA, +/- 6% Accuracy. Ergonomic multi-component handle, light & compact. Handle sizes proportioned to optimize torque range. Audible & perceptible click when torque setting has been attained.

Item	Range	↔	↔	↔
No.	Inch lbs.	Increments	mm	lbs. pkg.
WH28724	7.5 - 20	.5 Inch lbs	126 - 131	.43 1
WH28726	10 - 50	2 Inch lbs	133 - 138	.40 1
WH28727	20 - 70	2 Inch lbs	137 - 142	.69 1

**WH287 Insulated TorqueVario-S Handle - In Newton Meter Scale**

Item	Range	↔	↔	↔
No.	Nm	mm	lbs.	pkg.
WH28734	0.6 - 2.0	131	.45	1
WH28736	1.0 - 5.0	138	.45	1
WH28737	2.0 - 8.0	142	.72	1

Each TorqueVario handle has unique serial number & certificate of calibration

⚡ 1000Volt



**WH28350 Insulated SlimLine Torque Blade Holder**

Chrome-vanadium-molybdenum steel. Through hardened black finish. ClicFix quick release holder securely locks bits.

Item	OAL	OAL	↔	↔
No.	mm	mm	Inch	lbs. pkg.
WH28350	6.0	170	6.7	.02 1

### Wiha Insulated TorqueControl & SlimLine Tool Sets



⚡ 1000Volt

**WH28791 8 Piece Insulated TorqueControl Set With Slotted & Phillips SlimLine Blades** Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes Insulated multi-component adjustable TorqueVario-S handle, 5 SlimLine blades, SlimLine blade holder & Torque adjustment tool.

Item No.	↔ lbs.
WH28791 <i>SlimLine</i> Slotted: 3.0, 4.0, 5.5mm	.87
<i>SlimLine</i> Phillips: #1, #2	
WH28726 - Handle Range 10-50 Inch/lbs.	
<i>SlimLine</i> Blade Holder	

With Certificate of Calibration



⚡ 1000Volt

**WH28792 16 Piece Insulated TorqueControl Set With SlimLine Blades** Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes Insulated multi-component adjustable TorqueVario-S handle, 13 SlimLine blades, SlimLine blade holder & Torque adjustment tool.

Item No.	↔ lbs.
WH28792 <i>SlimLine</i> Slotted: 4.0, 5.5, 6.5mm	1.27
<i>SlimLine</i> Phillips: #1, 2	
<i>SlimLine</i> Terminal Xeno: #1, 2	
<i>SlimLine</i> TORX®: T8, T10, T15, T20	
<i>SlimLine</i> Square: #1, 2	
WH28727 - Handle Range 20-70 Inch/lbs.	
<i>SlimLine</i> Blade Holder	

With Certificate of Calibration