



## Machine Screw Anchors PC 4520

Machine screw (lead) anchors: Performs well in a variety of concrete strengths, can be used in brick. Any head style screw can be used. The screw can be easily removed or loosened and retightened. Vibration does not affect the lead insert's hold on the concrete. Adapts well to hole size variations. Drill hole in concrete and drop anchor expander side down into hole. Place setting tool over anchor and hammer until set.

- Medium Duty
- Tool Not Included
- Caution! Always Wear Eye Protection

CAT NO	UPC	ANCHOR SIZE	DRILL SIZE	INSTALL TOOL	STD	MSTR	WT/STD	UNIT
MA2	29910	8-32	5/16"	ST2	100	1000	1.00#	C
MA3	29915	10-24	3/8"	ST3	100	1000	1.75#	C
MA5	29925	1/4-20	1/2"	ST5	100	600	4.50#	C
MA6	29930	5/16"	5/8"	ST6	50	300	3.90#	C
MA7	29935	3/8"	3/4"	ST7	50	300	7.00#	C
MA8	29940	1/2"	7/8"	ST8	50	300	9.50#	C

ST Tool must be used for proper installation (sold separately).



## "ST" Tools for MA Anchors PC 4530

"ST" tool must be used for proper installation. Sold separately from MA anchors

CAT NO	UPC	SIZE	USE FOR	STD	MSTR	WT/STD	UNIT
ST2	17600	8-32	MA2	1	10	0.07#	Ea
ST3	17605	10-24	MA3	1	10	0.09#	Ea
ST5	17610	1/4-20	MA5	1	10	0.17#	Ea
ST6	17615	5/16"	MA6	1	10	0.27#	Ea
ST7	17620	3/8"	MA7	1	10	0.42#	Ea
ST8	17625	1/2"	MA8	1	10	0.53#	Ea



## Toggle Anchors - Nylon PC 4320

Nylon Toggle Anchors: After proper size hole is drilled, fold and insert anchor into hole. In solid concrete it will act as a conventional anchor, in hollow wall installations the anchor opens like a toggle bolt.

- Toggle Anchors
- Nylon
- Screws Not Provided
- Caution! Always Wear Eye Protection

CAT NO	UPC	SCREW/SIZE	DRILL SIZE	WALL THICKNESS	STD	MSTR	WT/STD	UNIT
NT14L	66790	8 x 1-1/2"	1/4"	1/2" Drywall	100	1000	0.26#	C
NT38L	66795	10 x 1-1/2"	3/8"	5/8" Drywall	100	1000	0.51#	C

See B15 For Kits ( NTK14L & NTK38L )



## Strap Toggle PC 4375

The Strap-Toggle is a heavy duty hollow wall anchor designed for use in base materials such as plaster, wallboard, or hollow tile. The Strap Toggle is a pre-assembled anchor consisting of a carbon steel wing and a locking cap/ratchet leg assembly molded from engineered plastic. It is available in both 3/16" and 1/4" size. When compared to traditional toggles, this unique anchor can be installed in a smaller hole and does not require a fixture or screw to set it. The anchor can be easily adjusted to accommodate a wall thickness of up to 2-1/2". The toggle remains captive.

- Strap Toggle
- Nylon
- Screws Not Provided
- Reusable
- Caution! Always Wear Eye Protection

CAT NO	UPC	SCREW/SIZE	DRILL SIZE	WALL THICKNESS	STD	MSTR	WT/STD	UNIT
ST36	10536	3/16 x 4"	1/2"	2-1/2"	50	250	1.64#	C
ST25	10525	1/4 x 4"	1/2"	2-1/2"	50	250	1.66#	C

See B15 For Kits

