








PLASTICS SAFE CONTACT CLEANER



EL™ 2020

-  For use on Electrical Circuitry
-  Dielectric strength value: 19,000 volts
-  NSF® Registered; K2 Rated (Solvents for cleaning electronic instruments) (Registration # 127506)
-  Non-flammable
-  Will not harm plastic
-  KB Solvency Strength (higher value, stronger the solvent): 56
-  HMIS Hazard Rating: Health (2) • Flammability (0) • Reactivity (0)

- Alternative to TF113®
- Dielectric strength: 19,000 volts
- Leaves no residue
- Very fast evaporation rate



PRESERVE. PROTECT. PREVENT.™

Sprayon® EL™ 2020 Plastics Safe Contact Cleaner is a fast-evaporating, non-flammable electronic/electrical cleaner that leaves no residue. This alternative to TF113® is safe on all metals and most plastics. May be applied while equipment is operating. Equipped with extension tube for pinpoint application. Dielectric strength of 19,000 volts, makes EL™ 2020 Plastics Safe Contact Cleaner suitable for a wide range of applications.

ELECTRICAL & ELECTRONIC

USES

- Computer systems & memory devices
- Printed circuits
- Meters
- Satellite communications & radar equipment
- Vacuum tube parts
- Typewriters & office machines
- Hydraulic & missile fuel systems
- Relays & switches
- Electronic games (TV/radio)
- Timing devices
- X-ray equipment
- Cameras (movie & 35mm)
- Precision instruments
- Telephone switch gears
- Coin counters & chutes



EL2020

APPLICATION

Product should be sprayed in a well ventilated area. Works best at room temperature (70°F). Hold can in upright position for best spray pattern. Use extension tube for pinpoint application.

PERFORMANCE

- EVAPORATION RATE: Very Fast
KB VALUE (Cleaning Power): 56
DIELECTRIC STRENGTH: 19,000 volts
PLASTIC SAFE: Yes
- NSF Registration Number 127506; K2 Rated
 - Quick evaporating
 - No residue
 - Alternative to TF-113®
 - Equipped with an extension tube for hard-to-reach areas

PACKAGING

STOCK #: S02020
UPC CODE: 0-75577-02020-1
FILL WT: 12 oz.
PER CASE: 12
CARTON DIMENSIONS:
L 11.13" x W 8.44" x H 8.38"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

PROPERTIES

APPEARANCE: Clear Volatile Liquid
ODOR: Sweet/Strong
PROPELLANT: 134A
WT./GAL.: 11.16
SPECIFIC GRAVITY: 1.34
H.A.P.S. (HAZARDOUS AIR POLLUTANTS): No
SARA 313 CHEMICALS: No
PROP 65: No
% VOC AEROSOL: 5%
V.O.C. COMPLIANT CALIFORNIA: Yes
V.O.C. COMPLIANT OTC STATES: Yes
FLAMMABLE: No
FLASH POINT: N/A
HAZARD RATING: 2,0,0
SHELF LIFE: 3 years from date of manufacture

RESOURCES

MSDS/EDS/PRODUCT DATA
SHEETS: sprayon.com
CUSTOMER SERVICE: 1-800-777-2966
TECHNICAL INFORMATION: 1-800-251-2486



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-EL2020