

Hub Covers

For GUA Outlet Boxes

Type GUAHC

Use:

Provides NPT thread hub for mounting pendant light fixtures (luminaires) on 1/2", 3/4" and 1" trade size Type GUA outlet boxes.

Features:

- O-Ring gasket provided to assure watertightness.
- Tapered threaded hub (NPT)
- Provided with anti-rotation set-screws.
- Maximum weight capacity: 50 lbs. per NEC Section 314-27(B).


Material/Finish:


Malleable Iron/Zinc Electroplated
Steel Set Screws
Buna-N O-Ring

Optional Finish:

Hot Dip or Mechanical Galvanized.
Add suffix "G" to standard catalog number.
Contact your local representative for pricing and availability.

Third Party Certification:

-  UL Listed: E-97032
Class I, Div. 1, 2, Groups C, D
Class I, Zone 1, 2, Groups IIA, IIB
Class II, Div. 1, 2, Groups E, F, G
Class III
Suitable for wet locations

-  CSA Certified: 020945

Applicable Third Party Standards:

UL Standard: 886
CSA Standard: C22.2 No. 30
NEC Articles 500-503 & 505
Mil. Spec: Mil-F-28675
Fed. Spec: A-A-50563


Suggested Specifications:

Where accessory covers for hazardous location outlet boxes are required for sealing, increasing volume or mounting pendant lighting fixtures (luminaires), they shall be malleable iron construction and UL Listed. These accessory covers shall be O-Z/Gedney Type GUASC, GUATE, GUADC, GUAFC or GUAHC.

Note:

GUAHE-50 and GUAHC-75 are suitable for use with 1/2", 3/4" and 1" trade size Type GUA malleable iron outlet boxes only. See page BA18.

Hub Trade Size (inches)	Catalog Number	Dimensions in Inches	
		Max. Dia. C	A
1/2	GUAHC-50	3 1/2	1 5/8
3/4	GUAHC-75	3 1/2	1 7/8



TYPE GUA OUTLET BOX - PAGE BA18

