

:: Products
:: Custom Products
:: Featured Products
:: Online Catalog
:: Order Tracking/ Expediting
:: Sales Locator
:: Sales Login
:: Other Useful Websites
:: Quality Policy
:: Catalog/Sample Request
:: Customer Satisfaction Survey

ONLINE CATALOG

Search Catalog

By Item #

All Categories Bushing

[Shopping Cart](#)

[Request for Quote](#)

[All Categories](#) > [Tuff-Seal™](#) > [Wire Mesh Grips](#) - > [Wide Range Strain Relief Grips](#) > [1 Grips](#) > [Bushing](#) > [Item # SRB-104](#)

Item # SRB-104 Bushing

\$1.15



[larger image](#)

Bushing

Tuff Seal™ RSR Series Aluminum Cord Grips are UL Listed and CSA Certified for use in both indoor and outdoor applications to prevent cable pullout, control arc at bend, and to provide a tight seal against environmental elements such as dirt, moisture and coolants.

The breadth of the line encompasses conduit sizes from 1/4" to 3" with fittings offered in machined aluminum, nickel-plated aluminum, steel, stainless steel, nylon and Valox®. Other features of the family of RSR Cord Grip include:

- ✦ A unique design with a combination tightening surface that includes both a hex area and a knurled surface.
- ✦ Available with or without wire mesh.
- ✦ Optional embedded Viton® O-Ring ensures a watertight and corrosion-resistant seal.
- ✦ Available in NPT, Pg/ISO or Metric threads.
- ✦ Anti-friction washer that fits between the nut and bushing for easier compression.

For applications known for their severe conditions - su

as oil and gas, marine, food & chemical processing - RSR Cord Grips are available in nickel-plated aluminum. Providing exceptional corrosion resistance and high wear resistance, nickelplated connectors also feature an attractive finish similar to that of polished stainless steel. Tuff Seal RSR Cord Grips protect cable from damage and pull-out and are used in conduit hubs or knockouts at the point where the electrical cable is to be terminated.

These connectors are UL Listed, CSA Certified and ROHS Compliant.

Specifications	<u>Tuff-Seal Custom Capabilities</u>
Cable Range	0.188 - 0.250
Weight per 100 Piece	1.4 lbs.
UPC 785411	10104

[Request Information](#) [Add To Cart](#) [Request Quote](#)

[Products](#) | [Custom Solutions](#) | [Did You Know?](#) | [Order Tracking / Expediting](#) | [Sales Locator](#) | [About Us](#) | [What's New](#) | [Site Map](#) | [Contact Us](#) | [Other Useful Websites](#) | [Quality Policy](#)

© REMKE 2006. ALL RIGHTS RESERVED | **TOLL FREE: 877.438.8833** | PHONE: 847.541.3780 | FAX: 847.541.7242
Remke Industries - 310 Chaddick Drive - Wheeling, IL 60090