

401504 -- Copper-Coat® Gasket Compound, 4 Fl Oz**Product Description**

High temperature, high quality gasket sealer. Prevents compression loss on paper, cork and premium gaskets. Dauber built into the lid for easy application and storage.

Product Specifications**Applications**

Automatic transmissions, cover plates, diesel heads, high compression engines, hi-speed turbine superchargers, hydraulic pumps

Unit Package Description

4 ounce Brush Top Bottle

Brand

K&W

Generic Description 1

Gasket Compound

Net Fill

4 Fl Oz

UPC Code

078372015045

Unit Dimensions

2.75H x 2.5W x 2.5D in

Units Per Case

12

Case Dimensions

3.7H x 6.8W x 8D in

Cases Per Pallet

280

Case Weight

5 lbs

I 2 of 5 Code

10078372015042

Appearance

Viscous Copper Liquid

Odor

Hydrocarbon

Flashpoint

30°F

Flammability

Flammable

Specific Gravity

0.74

Plastic Safe

Yes

Evaporation Rate

>1 (butyl acetate=1)

Dielectric Strength

Not Determined

Working Temp

-80 to 400°F

Propellant

None

DOT Proper Shipping Name

Consumer Commodity

VOC % (Federal)

74.2

VOC g/L (Federal)

549

VOC Lbs./Gal. (Federal)

4.57

VOC Category

Not Regulated

Removal (How To)

Gasket remover