

SL3110 -- New Generation™ Wheel Bearing Grease for Disc and Drum Brakes, 14 Wt Oz**Product Description**

A premium lithium complex NLGI grade 2 grease with drop point of over 500° F. This grease is designed for late model vehicles wheel bearings, chassis, suspension & u-joints. Wide temperature range -40°F to 300°F. Extreme pressure additives.

Product Specifications

Applications	Automotive applications, ball joints, bearings, chassis points, construction ball & roller bearings, conveyor bearings, disc-brake systems, farm equipment, guides, mining applications, press rolls, roller bearings, slides, wheel bearings
Unit Package Description	14 Ounce Cartridge
Brand	Sta-Lube
Generic Description 1	Wheel Bearing Grease
Net Fill	14 Wt Oz
UPC Code	072213311006
Unit Dimensions	9.31H x 2.13W x 2.13D in
Units Per Case	10
Case Dimensions	9.5H x 4.5W x 11.38D in
Cases Per Pallet	150
Case Weight	11 lbs
I 2 of 5 Code	30072213311007
Appearance	Amber Semi-Solid to Solid Grease
Odor	Faint Petroleum
Base Type	Lithium Complex
Flashpoint	450°F
Flammability	Non-flammable
Specific Gravity	0.9 at 60°F
NLGI Grade	2
Timken OK Load [Lbs.]	50 Lbs
Plastic Safe	Not Determined
Evaporation Rate	<1 (butyl acetate=1)
Working Temp	-40 to 325°F
4 Ball EP	250 KG Weld,45 LWI
4 Ball Wear	0.6 mm
Drop Point	500°F
Leakage	6
Low Temp Torque	15.5 Max
Oil Separation	3.5
Oxidation Stability	5
Pour Point	Not Determined
ISO Viscosity Grade	150
Water Washout	7
Worked Penetration	265 to 295
Propellant	None
NSF Registered	No
DOT Proper Shipping Name	Not Regulated
VOC % (Federal)	1
VOC g/L (Federal)	9
VOC Lbs./Gal. (Federal)	0.075
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.