SL3131 -- Heavy Duty Drum Brake Wheel Bearing Grease, 14 Wt Oz



## **Product Description**

A sodium-based short fiber grease for autos & trucks with drum brake systems and slow speed industrial bearings. Meets most demands for economical wheel bearing lubrication. Good adhesive characteristics.

Product Specifications

**Applications** Drum brake systems, for use where heavy

loads & slow speeds are present

Unit Package Description 14 Ounce Can Brand Sta-Lube

Generic Description 1 HD Drum Brake Wheel Bearing Grease

**Net Fill** 14 Wt Oz **UPC Code** 072213313109

**Unit Dimensions** 3.44H x 4.13W x 4.13D in

Units Per Case 12

Case Dimensions 3.5H x 12.5W x 17D in

Cases Per Pallet 108
Case Weight 13 lbs

**I 2 of 5 Code** 30072213313100

**Appearance** Amber Semi-Solid to Solid Grease

**Odor** Faint Petroleum

**Base Type** Sodium Flashpoint >450°F

Flammability Non-flammable
Specific Gravity 0.9 at 60°F
NLGI Grade 2.5

Timken OK Load [Lbs.] Not Determined Plastic Safe Not Determined

**Evaporation Rate** <0.01 (Butyl Acetate=1)

Working Temp 10 to 250°F 4 Ball Wear Not Determined

**Drop Point** 360°F

Leakage Not Determined
Low Temp Torque Not Determined

Oil Separation <10
Oxidation Stability 5 Lbs
Pour Point 0°F (oil)
ISO Viscosity Grade 190
Worked Penetration 240 to 260
Propellant None
NSF Registered No

**DOT Proper Shipping Name** Not Regulated

VOC % (Federal) 0 VOC g/L (Federal) 0 VOC Lbs./Gal. (Federal) 0

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner

product.