


SL3141 -- Moly-Graph® Extreme Pressure Multi-Purpose Grease, 14 Wt Oz

**Product Description**

Extreme pressure MOLY-GRAPH Multi-Purpose Grease is the best general purpose grease for a wide range of applications. It offers an excellent mechanical and shear stable Lithium 12 Hydroxy Protection of "moly" and graphite. Timken load of 40 lbs.

Product Specifications**Applications**

Automotive applications, backing plates, ball joints, chassis points, construction ball & roller bearings, idler bearings, industrial applications, mining applications, pillow block bearings, sprocket bearings, U-joints, water pumps, wheel bearings

Unit Package Description

14 Ounce Can

Brand

Sta-Lube

Generic Description 1

E. P. Multi-Purpose Lithium Grease

Net Fill

14 Wt Oz

UPC Code

072213314106

Unit Dimensions

3.44H x 4.13W x 4.13D in

Units Per Case

12

Case Dimensions

3.5H x 12.5W x 17D in

Cases Per Pallet

108

Case Weight

13 lbs

I 2 of 5 Code

30072213314107

Appearance

Grey Semi-Solid to Solid Grease

Odor

Faint Petroleum

Base Type

Lithium-12

Flashpoint

>400°F

Flammability

Non-flammable

Specific Gravity

0.9 at 60°F

NLGI Grade

2

Timken OK Load [Lbs.]

45 Lbs Min

Plastic Safe

Not Determined

Evaporation Rate

<0.01 (Butyl Acetate=1)

Working Temp

-25 to 250°F

4 Ball EP

250 KG Weld,30 LWI

4 Ball Wear

0.6 mm typical

Drop Point

350°F

Elastomer Compatibility

0 to 40% vol ; 0 to 15 hard

Leakage

5

Low Temp Torque

15.5 Max

Oil Separation

<10%

Oxidation Stability

5

Pour Point

0°F

ISO Viscosity Grade

165

Water Washout

<15%

Worked Penetration

265 to 295

Propellant

None

NSF Registered

No

DOT Proper Shipping Name

Not Regulated

VOC % (Federal)

0.2

VOC g/L (Federal)

1.8

VOC Lbs./Gal. (Federal)

0.015

VOC Category

Not Regulated

Removal (How To)

Remove with a degreaser or brake cleaner product.