

SL3311 -- Lithium General Purpose Grease, 14 Wt Oz**Product Description**

A high purity, NLGI Grade 2 lithium based grease. Provides superior lubrication & durability in any weather and most temperatures. It is a versatile grease designed for light duty applications requiring a long grease life. Will not break down or run out.

Product Specifications**Applications**

Hinges, latches, overhead door tracks, open gears, chains, cables, slide conveyors, guide rails, cams, pistons, machinery, tools, & equipment. A break-in lubrication for bearings.

Unit Package Description

14 Ounce Can

Brand

Sta-Lube

Generic Description 1

Lithium General Purpose Grease

Net Fill

14 Wt Oz

UPC Code

072213331103

Unit Dimensions

3.44H x 4.13W x 4.13D in

Units Per Case

12

Case Dimensions

3.5H x 12.5W x 17D in

Cases Per Pallet

108

Case Weight

14 lbs

I 2 of 5 Code

30072213331104

Appearance

Amber Semi-Solid to Solid Grease

Odor

Petroleum

Base Type

Lithium-12

Flashpoint

450°F

Flammability

Non-flammable

Specific Gravity

0.9 at 60°F

NLGI Grade

2

Timken OK Load [Lbs.]

Not Determined

Plastic Safe

Not Determined

Evaporation Rate

<0.01 (Butyl Acetate=1)

Working Temp

0 to 300°F

4 Ball EP

Not Determined

4 Ball Wear

Not Determined

Drop Point

350°F

Oil Separation

<10%

Oxidation Stability

5

Pour Point

-15°F

ISO Viscosity Grade

150

Water Washout

<15%

Worked Penetration

265 to 295

Propellant

None

NSF Registered

No

DOT Proper Shipping Name

Not Regulated

VOC % (Federal)

<0.1

VOC g/L (Federal)

<0.9

VOC Lbs./Gal. (Federal)

<0.01

VOC Category

Not Regulated

Removal (How To)

Remove with a degreaser or brake cleaner product.