

**SL3333 -- Extreme Pressure Engine Assembly Lube, 2.75 Wt Oz****Product Description**

Engine Assembly lube is a lithium 12 hydroxy stearate based grease which adheres to metal surfaces to prevent destructive metal to metal contact. Prevents friction, galling and wear on all types of engines.

**Product Specifications****Applications**

The assembly of all mechanical parts. Lubricating areas of rotation sliding contact, such as cylinders, crank shafts and cam shafts. Also recommended for coating internal engine parts during assembly

**Unit Package Description**

2.75 Ounce Tube

**Brand**

Sta-Lube

**Generic Description 1**

Anti-Seize Engine Assembly Lube

**Net Fill**

2.75 Wt Oz

**UPC Code**

07221333305

**Unit Dimensions**

8.5H x 5W x 1.5D in

**Units Per Case**

12

**Case Dimensions**

9.06H x 5.13W x 9D in

**Cases Per Pallet**

205

**Case Weight**

3 lbs

**I 2 of 5 Code**

3007221333306

**Appearance**

Black Semi-Solid to Solid Grease

**Odor**

Faint Petroleum

**Base Type**

Lithium-12 Hydroxy

**Flashpoint**

450°F

**Flammability**

Non-flammable

**Specific Gravity**

0.9 at 60°F

**Plastic Safe**

Yes

**Evaporation Rate**

<0.01 (Butyl Acetate=1)

**Working Temp**

0 to 250°F

**Propellant**

None

**NSF Registered**

No

**DOT Proper Shipping Name**

Not Regulated

**VOC % (Federal)**

<0.1

**VOC g/L (Federal)**

<0.9

**VOC Lbs./Gal. (Federal)**

<0.007

**VOC Category**

Not Regulated

**Removal (How To)**

Remove with a degreaser or brake cleaner product.