SL3361 -- White Lube All Purpose Lithium Grease, 1.75 Wt Oz



## **Product Description**

A high purity, NLGI Grade 2 multi-purpose white lithium grease. Provides superior lubrication & durability in any weather and most temperatures. Bright white in color. Ideal for when appearance is important.

## **Product Specifications**

**Applications** Assembly lubes, bearings, break-in lubrication for

bearings, cables, chains, chassis points, conveyor bearings, door tracks, garage door channels & openers, hinges, latches, machinery, open gears, overhead door

tracks, roller bearings, sleeve bearings.

**Unit Package Description** 1.75 Ounce Squeeze Tube

Sta-Lube **Generic Description 1** White Lube Net Fill 1.75 Wt Oz **UPC Code** 072213336108

**Unit Dimensions** 1.19H x 1.44W x 7.06D in

**Units Per Case** 24

7.63H x 6.38W x 7.5D in **Case Dimensions** 

Cases Per Pallet 185 Case Weight 4 lbs

I 2 of 5 Code 30072213336109

**Appearance** White Semi-Solid to Solid Grease

Odor Faint Petroleum Base Type Lithium-12 Flashpoint 475°F Flammability Non-flammable Specific Gravity 0.9 at 60°F

1.5 **NLGI Grade** Timken OK Load [Lbs.] 25 Lbs

Plastic Safe Not Determined

**Evaporation Rate** <0.01 (Butyl Acetate=1)

0 to 300°F **Working Temp** 4 Ball EP Not Determined 4 Ball Wear 0.6 mm (max) **Drop Point** 350°F

Not Determined Leakage **Low Temp Torque** Not Determined

Oil Separation **Oxidation Stability** 10 **Pour Point** 0°F **ISO Viscosity Grade** 165 Water Washout <15% Worked Penetration 285 to 295 **Propellant** None **NSF Registered** No

Not Regulated **DOT Proper Shipping Name** 

VOC % (Federal) < 0.1 < 0.9 VOC g/L (Federal) VOC Lbs./Gal. (Federal) < 0.01

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.