



Product Description

A synthetic, dry-film, ceramic lubricant formulated to reduce brake noise and vibrations by dampening all brake vibrating frequencies. Will not run off or wash out. Works in extreme temp ranges from -50 to 3000°F. Protects against uneven pad wear.

Product Specifications

Applications

All brake systems and brake components, including calipers, bushings, holes, pins, inserts, anchors, bolts, calipers and boots

Unit Package Description

9 Ounce Tub with Brush

Brand

CRC

Generic Description 1

Brake System Grease

Net Fill

9 Wt Oz

UPC Code

078254053639

Unit Dimensions

4.25H x 3.88W x 3.88D in

Units Per Case

12

Case Dimensions

5H x 12.25W x 16D in

Cases Per Pallet

175

Case Weight

8 lbs

I 2 of 5 Code

30078254053630

Appearance

Off White Semi Solid Grease

Odor

Mild

Base Type

Polydimethylsiloxane

Flashpoint

550°F

CPSC Flammability Class

None

Specific Gravity

1.0

NLGI Grade

2

Timken OK Load [Lbs.]

Not Determined

Plastic Safe

Yes

Evaporation Rate

Very Slow

Dielectric Strength

Not Determined

Working Temp

-50 to 3000°F

4 Ball EP

Not Determined

4 Ball Wear

Not Determined

Drop Point

None

Elastomer Compatibility

Compatible

Leakage

0.2

Low Temp Torque

Not Determined

Oil Separation

0.2

Oxidation Stability

Not Determined

Pour Point

Not Determined

Water Washout

0.25

Worked Penetration

265 to 295

Propellant

None

NSF Registered

No

DOT Proper Shipping Name

Not Regulated

VOC % (Federal)

0

VOC g/L (Federal)

0

VOC Lbs./Gal. (Federal)

0

VOC Category

Not Regulated

Removal (How To)

Remove with petroleum solvents.