

2900HA Series Electric Baseboard - High Altitude Convection Heater



Manufactured in U.S.A.

Features

- Available in white or ivory with Aluminum heating element and Aluminum fins.
- Painted 22 Gauge steel front with 20 Gauge junction boxes located on each end of the heater - junction boxes contain quick connect cable clamps and 6" ground lead wires.
- Over-temperature thermal limit extends entire length of heated area.
- A full length wireway provided along the back of the heater.
- Optional enclosed conduit wireway available.
- Heater can be mounted to the wall by using the key hole knockouts every 4" at the back of the heater.
- Optional In-Built thermostats field installed in the junction box.
- HEIGHT: 6" DEPTH: 2-1/2"
- Ivory available with extended lead times-consult factory.

Standard Models

UPC# 686334	WHITE MODEL	WATTS	BTU's	VOLTS	AMPS	HEATER LENGTH (IN)	WT. (LBS.)	LIST
101226	E2903-024HAW	375	1275	120	3.1	24	5	62
101233	F2903-024HAW	375	1275	208	1.8			
101240	H2903-024HAW	375 / 281	1275 / 955	240 / 208	1.6/1.4			
101257	G2903-024HAW	375 / 281	1275 / 955	277 / 240	1.6/1.2	28	6	64
101264	E2905-028HAW	500	1706	120	4.2			
101271	F2905-028HAW	500	1706	208	2.4			
101288	H2905-028HAW	500 / 375	1706 / 1275	240 / 208	2.1/1.8	36	7	71
101295	G2905-028HAW	500 / 375	1706 / 1275	277 / 240	1.8/1.6			
101301	E2906-036HAW	600	2040	120	5			
101318	F2906-036HAW	600	2040	208	2.9	40	8	74
101325	H2906-036HAW	600 / 450	2040 / 1530	240 / 208	2.5/2.2			
101332	G2906-036HAW	600 / 450	2040 / 1530	277 / 240	2.2/1.9			
101349	E2907-040HAW	750	2550	120	6.3	48	10	89
101356	F2907-040HAW	750	2550	208	3.6			
101363	H2907-040HAW	750 / 563	2550 / 1914	240 / 208	3.1/2.7			
101370	G2907-040HAW	750 / 563	2550 / 1914	277 / 240	2.7.2.6	60	12	111
101387	E2910-048HAW	1000	3413	120	8.3			
101394	F2910-048HAW	1000	3413	208	4.8			
101400	H2910-048HAW	1000 / 750	3413 / 2550	240 / 208	4.2/3.6	72	14	125
101417	G2910-048HAW	1000 / 750	3413 / 2550	277 / 240	3.6/3.1			
101424	G2907-048HAW	750	2550	277	3.4			
101431	E2912-060HAW	1250	4250	120	10.4	96	18	153
101448	F2912-060HAW	1250	4250	208	6			
101455	H2912-060HAW	1250 / 938	4250 / 3189	240 / 208	5.2/4.5			
101462	G2912-060HAW	1250 / 938	4250 / 3189	277 / 240	4.5/3.9	120	22	169
101479	G2909-060HAW	938	3189	277	3.4			
101486	E2915-072HAW	1500	5100	120	12.5			
101493	F2915-072HAW	1500	5100	208	7.2	96	18	153
101509	H2915-072HAW	1500 / 1125	5100 / 3825	240 / 208	6.3/4.7			
101516	G2915-072HAW	1500 / 1125	5100 / 3825	277 / 240	5.4/4.7			
101523	G2911-072HAW	1125	3825	277	4.1	120	22	169
101578	F2920-096HAW	2000	6826	208	9.6			
101585	H2920-096HAW	2000 / 1500	6826 / 5100	240 / 208	8.3/7.2			
101592	G2920-096HAW	2000 / 1500	6826 / 5100	277 / 240	7.2/6.3	120	22	169
101608	G2915-096HAW	1500	5100	277	5.4			
101653	F2925-120HAW	2500	8532	208	12			
101660	H2925-120HAW	2500 / 1875	8532 / 6375	240 / 208	10.4/9.0	120	22	169
101677	G2925-120HAW	2500 / 1875	8532 / 6375	277 / 240	9.0/7.8			
101684	G2918-120HAW	1875	6375	277	6.8			

2900A Series - International Models

UPC# 686334	WHITE MODEL	WATTS	BTU's	VOLTS	HEATER LENGTH (IN)	WEIGHT (LBS)	LIST
115766	M2903-24AWi	375	1275	220	24"	10	81
115773	H2903-24AWi			240			
115780	M2905-28AWi	500	1706	220	28"	11	84
115977	H2905-28AWi			240			
115803	M2906-36AWi	600	2040	220	36"	11.5	93
115810	H2906-36AWi			240			
115827	M2907-40AWi	750	2550	220	40"	13	97
115834	H2907-40AWi			240			
115841	M2910-48AWi	1000	3413	220	48"	14	116
115858	H2910-48AWi			240			
115865	M2912-60AWi	1250	4250	220	60"	16	145
115872	H2912-60AWi			240			
115889	M2915-72AWi	1500	5100	220	72"	19	163
115896	H2915-72AWi			240			
115902	M2917-84AWi	1750	5950	220	80"	22	199
118002	H2917-84AWi			240			
118033	M2925-120AWi	2500	8532	220	120"	31	220
118040	H2920-120AWi			240			

Wireway Length Same As Baseboard Length