

Industrial Ceiling Fans



Features

- All metal construction, white epoxy finish
- 24" down rod with safety cable, 36" available for additional charge.
- Mounts to 3/8" diameter steel J-hook
- 18 pole (motor), 115V, 1-Phase, capacitor type, impedance protected motor with sealed ball bearings

Note: Photograph is a representation of stocked models. Actual model may vary in appearance.

Commercial Grade

- Assembly required
- 30" lead wires
- 1 year limited warranty

Industrial Grade

- Fully assembled except blade bolt down
- 3 conductor cord, 30" long with plug
- Permanently lubricated
- 3 year limited warranty

Heavy Duty Grade

- Fully assembled except blade bolt down
- 3 conductor cord, 30" long with plug
- Permanently lubricated
- 6 year limited warranty

Standard Models

| GRADE | UPC# 686334 | MODEL | TYPE | SIZE | VOLTS | CFM | RPM | AMPS | WT. (LBS.) | LIST |
|---------------------------------|-------------|--------------|------------|------|-------|-------|-----|------|------------|------|
| Commercial | 852968 | CHR-56 | Down Draft | 56" | 120 | 19000 | 320 | 0.6 | 15 | 170 |
| Industrial | 797993 | IHR-48 | Down Draft | 48" | 120 | 17100 | 320 | 0.53 | 14 | 230 |
| Industrial | 797153 | IHR-56 | Down Draft | 56" | 120 | 21000 | 310 | 0.6 | 15 | 242 |
| Industrial | 798006 | IHR-56R | Reversible | 56" | 120 | 21000 | 310 | 0.55 | 14 | 247 |
| Industrial | 800891 | IHR-56-277V* | Down Draft | 56" | 277 | 21000 | 310 | 0.3 | 16 | 247 |
| Heavy Duty | 851527 | HDHR-56 | Down Draft | 56" | 120 | 27500 | 320 | 0.75 | 18 | 315 |
| Heavy Duty | 799393 | HDHR-60 | Down Draft | 60" | 120 | 47000 | 320 | 0.8 | 21 | 358 |
| Water and Dust Resistant Models | | | | | | | | | | |
| Heavy Duty | 854085 | HDHR-56WR | Down Draft | 56" | 120 | 27500 | 320 | 1.1 | 17 | 340 |
| Heavy Duty | 854092 | HDHR-60WR | Down Draft | 60" | 120 | 47000 | 320 | 0.8 | 21 | 384 |

* 277 volt, commercial, and reversing models have lead wires instead of cordset.

Solid State Controls (120 & 277V Models)

| 120V | | | 277V | | TYPE | LIST |
|-------------|----------|------|-------------|--------------|-------------------------|------|
| UPC# 686334 | MODEL | LIST | UPC# 686334 | MODEL | | |
| 797634 | HR-SS-2 | 44 | ----- | ----- | 1-2 FANS SPEED CONTROL | 44 |
| 797641 | HR-SS-5 | 88 | 852654 | HR-SS-10-277 | 6-10 FANS SPEED CONTROL | 300 |
| 799416 | HR-SS-10 | 156 | | | | |

Solid State Controls & Reversing Switch for IHR-56R

| UPC# 686334 | MODEL | TYPE | LIST |
|-------------|----------|---|------|
| 866682 | HR-RSS-3 | 1-3 FANS REVERSING SWITCH and SPEED CONTROL | 143 |

Options

| UPC# 686334 | MODEL | TYPE | LIST |
|-------------|-------------|---------------------|-----------|
| 851220 | HR-GUARD | FOR 56" MODELS | 947 |
| 850421 | Suffix - X3 | 36" DOWN ROD OPTION | +45 Adder |

Portable 18" Self Contained Power Mister

SELF CONTAINED MISTING SYSTEM WITH WATER PUMPED FROM A 10 GALLON TANK OR VESSIL.

Features

- Toggle Switch - fan only or fan & mist
- SJT type cord - 3 conductor - 18' long with GFCI plug
- 18" Aluminum blade
- Spiral front and rear wire guards
- 85 PSI diaphragm pump
- Meets OSHA standards / 1 year limited warranty.

Motor Specification

- 1-Speed, 1/8 HP
- Sleeve bearing
- Permanently lubricated
- 1-Phase, 120 Volt
- Totally enclosed
- Permanent split capacitor



PM-18C



PM-18S

Note: Cooler lid not included.



PM-18FO

Standard Features

| UPC# 686334 | MODEL | FAN SIZE | TYPE | MOTOR HP | CFM | AMPS | WT. (LBS) | LIST |
|-------------|--------|----------|------------|----------|------|------|-----------|------|
| 855471 | PM-18S | 18" | HAND CARRY | 1/8 | 5750 | 2.2 | 30 | 1046 |
| 855495 | PM-18C | | CART | | | | 76 | 1331 |

18" Fan & Pump Lid for 10gal. Cooler

| UPC# 686334 | MODEL | SHIPPING WT. (LBS.) | LIST |
|-------------|---------|---------------------|------|
| 855525 | PM-18FO | 28 | 897 |