

# ProLume. Covered Spirals - Quick Reference Guide

Bulb Type	Base	Product #	Product Code	Description	Pkg Qty	Color Temp	CRI	Initial Lumens	Incandescent Equivalent	Life	MOL (Inc)	MOD (Inc)
<b>5 Watts</b>												
A16	Med.	45730	CFL5/27/A16	Warm White	10/50	2700	82	250	25	8000	4.07"	2.13"
A16	Med.	45732	CFL5/41/A16	Cool White	10/50	4100	82	250	25	8000	4.07"	2.13"
B13	Cand.	45762	CFL5/30/B13/E12	Soft White	10/50	3000	82	200	25	8000	3.86"	1.57"
B13	Med.	45761	CFL5/30/B13	Soft White	10/50	3000	82	200	25	8000	3.86"	1.57"
<b>9 Watts</b>												
A16	Med.	45734	CFL9/27/A16	Warm White	10/50	2700	82	470	40	10000	4.50"	2.20"
B13	Cand.	45764	CFL9/30/B13/E12	Soft White	10/50	3000	82	470	40	8000	4.43"	1.61"
B13	Med.	45763	CFL9/30/B13	Soft White	10/50	3000	82	470	40	8000	4.43"	1.61"
G25	Med.	45703	CFL9/27/G25/ES	Warm White	6/24	2700	82	500	40	10000	4.33"	3.11"
G25	Med.	45705	CFL9/50/G25	Natural White	6/24	5000	82	500	40	10000	4.33"	3.11"
<b>11 Watts</b>												
PAR20	Med.	46005	CFL11/27/PAR20	Warm White Flood	6/24	2700	82	380	50	10000	3.86"	2.48"
PAR20	Med.	46006	CFL11/35/PAR20	White Flood	6/24	3500	82	380	50	10000	3.86"	2.48"
PAR20	Med.	46007	CFL11/41/PAR20	Cool White Flood	6/24	4100	82	380	50	10000	3.86"	2.48"
PAR20	Med.	46008	CFL11/50/PAR20	Natural White Flood	6/24	5000	82	380	50	10000	3.86"	2.48"
R20	GU24	46542	CFL11/27/R20/GU24	Warm White Flood	6/24	2700	82	340	50	10000	4.02"	2.50"
<b>14 Watts</b>												
A19	Med.	45738	CFL14/27/A19	Warm White	10/50	2700	82	800	60	10000	4.63"	2.28"
A19	Med.	45739	CFL14/35/A19	White	10/50	3500	82	800	60	10000	4.63"	2.28"
A19	Med.	45740	CFL14/41/A19	Cool White	10/50	4100	82	800	60	10000	4.63"	2.28"
A19	Med.	45741	CFL14/50/A19	Natural White	10/50	5000	82	800	60	10000	4.63"	2.28"
R20	Med.	46011	CFL14/30/R20	Soft White Flood	6/24	3000	82	500	50	8000	4.94"	2.52"
R20	Med.	46014	CFL14/50/R20	Natural White Flood	6/24	5000	82	500	50	8000	4.94"	2.52"
T20	Med.	45755	CFL14/27/T20	Warm White	6/24	2700	82	800	60	8000	5.44"	2.48"
T20	Med.	45758	CFL14/50/T20	Natural White	6/24	5000	82	800	60	8000	5.44"	2.48"
<b>15 Watts</b>												
A19	GU24	46540	CFL15/27/A19/GU24	Warm White	6/24	2700	82	800	60	10000	4.82"	2.64"
G25	GU24	46536	CFL15/27/G25/GU24	Warm White	6/24	2700	82	750	60	10000	4.80"	3.31"
G28	Med.	45713	CFL15/27/G28	Warm White	6/24	2700	82	850	60	10000	4.73"	3.43"
G28	Med.	45717	CFL15/50/G28	Natural White	6/24	5000	82	850	60	10000	4.73"	3.43"
PAR30	Med.	46001	CFL15/27/PAR30	Warm White Flood	6/24	2700	82	750	75	10000	4.60"	3.74"
PAR30	Med.	46550	CFL15/27/PAR30/DIM	Warm White Flood Dimmable	6/24	2700	82	700	75	10000	4.60"	3.74"
PAR30	Med.	90201	CFL15/27/PAR30/CS	Warm White Flood, CoverShield®	6/24	2700	82	750	75	10000	4.60"	3.74"
PAR30	Med.	46002	CFL15/35/PAR30	White Flood	6/24	3500	82	750	75	10000	4.60"	3.74"
PAR30	Med.	46003	CFL15/41/PAR30	Cool White Flood	6/24	4100	82	750	75	10000	4.60"	3.74"
PAR30	Med.	46004	CFL15/50/PAR30	Natural White Flood	6/24	5000	82	750	75	10000	4.60"	3.74"
R30	GU24	46538	CFL15/27/R30/GU24	Warm White	6/24	2700	82	700	65	10000	4.76"	3.74"
R30	Med.	46328	CFL15/27/R30/DIM	Warm White Flood Dimmable	6/24	2700	82	680	65	8000	6.01"	3.74"
R30	Med.	109166	CFL15/50/R30/TF	Natural White, Safety Coated	1/24	5000	82	550	65	8000	5.38"	3.78"
<b>16 Watts</b>												
G30	Med.	45725	CFL16/27/G30	Warm White	6/24	2700	82	900	60	10000	5.07"	3.70"
G30	Med.	46533	CFL16/50/G30	Natural White	6/24	5000	82	900	60	10000	5.07"	3.70"
R30	Med.	46101	CFL16/30/R30/ES	Soft White Flood	6/24	3000	82	750	65	10000	5.60"	3.78"
R30	Med.	46104	CFL16/41/R30	Cool White Flood	6/24	4100	82	750	65	10000	5.60"	3.78"
R30	Med.	46105	CFL16/50/R30	Natural White Flood	6/24	5000	82	750	65	10000	5.60"	3.78"
<b>20 Watts</b>												
A20	Med.	45743	CFL20/27/A20	Warm White	6/24	2700	82	1100	75	8000	5.56"	2.80"
<b>23 Watts</b>												
BR38	Med.	109216	CFL23/30/BR38	Soft White Flood	6/24	3000	82	1300	100	10000	6.40"	4.72"
PAR38	Med.	46201	CFL23/27/PAR38	Warm White Flood	6/24	2700	82	1100	90	10000	5.06"	4.76"
PAR38	Med.	46202	CFL23/35/PAR38	White Flood	6/24	3500	82	1100	90	10000	5.06"	4.76"
PAR38	Med.	46203	CFL23/41/PAR38	Cool White Flood	6/24	4100	82	1100	90	10000	5.06"	4.76"
PAR38	Med.	46204	CFL23/50/PAR38	Natural White Flood	6/24	5000	82	1100	90	10000	5.06"	4.76"

# ProLume. Covered Spirals - Quick Reference Guide

Bulb Type	Base	Product #	Product Code	Description	Pkg Qty	Color Temp	CRI	Initial Lumens	Incandescent Equivalent	Life	MOL (Inc)	MOD (Inc)
<b>23 Watts</b>												
R40	Med.	46329	CFL23/27/R40/DIM	Warm White Flood Dimmable	6/24	2700	82	1090	100	10000	6.97"	5.00"
R40	Med.	109286	CFL23/30/R40	Soft White Flood	6/24	3000	82	1090	100	10000	6.50"	5.00"
R40	Med.	46206	CFL23/50/R40	Natural White Flood	6/24	5000	82	1090	100	10000	6.50"	5.00"

Represents lamps that are Energy Star approved.

 Hg-Lamp Contains Mercury, Manage In Accord With Disposal Laws.

Non-dimmable lamps should not be used on dimming circuits, timing devices, photo sensors or occupancy sensors. | This device is not intended for use with emergency exit fixtures. Dimmable lamps may not be compatible with all dimmers.