

## Group marker, Terminal markers SCHT 5 S

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



The **SchT 5 S** group tag carriers are clipped directly to the TS 32 DIN rail (G-rail) or the TS 35 DIN rail (top-hat rail). It is therefore possible to provide terminal strip labelling irrespective of the terminal and the type of terminal.

**SchT 5** and **SchT 5 S** are fitted with ESO 5, STR 5 protective strips.

Inlay tags and protective strips can be found under "Accessories".

### General ordering data

Order No.	<a href="#">1631930000</a>
Type	SCHT 5 S
Version	Group marker, Terminal markers, 44.5 x 9.5 mm, Polyamide 66, Colour: Beige
GTIN (EAN)	4008190206680
Qty.	20 pc(s).

**Group marker, Terminal markers  
SCHT 5 S**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

Length	44.5 mm	Width	9.5 mm
Net weight	3.64 g		

**Markings**

Can be labelled with thermal transfer printers	No	Can be printed with plotter	No
Can be written with dot-matrix printer	No	Can be written with laser printer	No
Colour	Beige	Conductor O.D.	
Material	Polyamide 66	Max. temperature, transient	80 °C
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Orientation of print	horizontal and vertical	Pitch in mm (P)	5 mm
Speed marking laser	No	UL 94 flammability rating	V-2

**Classifications**

ETIM 2.0	EC000761	ETIM 3.0	EC000761
UNSPSC	30-21-18-07	eClass 4.1	24-19-02-19
eClass 5.1	27-14-11-37	eClass 6.2	27-14-11-37
eClass 7.1	27-14-11-37		

**Product information**

**Product description** The SCHAT 5 & SCHAT 5 S group marker carrier is clipped directly to the TS 32 DIN rail (G-rail) or the TS 35 DIN rail (top-hat rail). It is therefore possible to provide terminal strip labelling irrespective of the terminal and the type of terminal.

**Approvals**

Approvals



ROHS Conform