## **MSDS LIST FOR NA PRODUCT**

Model: FV-0510VSC1 / FV-0510VSCL1 / FV-0510VSL1 FV-0810VSS1 / FV-0810VSSL1

ITEM	USED AT	FUNCTION	COMPONENT	RATIO
GRAIN ALCOHOL	All the Cleaning Process	Cleaning	Alcohol	100%
EA2	Shutter Assembling	Lubricate	Lubrication	80-90%
			Thicken Additive	10-20%
			Other Additive	2-7%
SRL LUBRICANT GREASE	Motor Assembling	Lubricate	Synthetic grease	100%
RUST VETO HEAVY	Motor Assembling	Rust prevention	Mineral oil	40%
			Paraffin	10%
			Solvent	5%
			Mahogany petroleum sulfonate	15%
			Composite antirust	20%
			Antioxidant	3%
			Preservative	7%
WHITE GAS	Injection molding process	Cleaning	Alkanes	100%
S-807 OIL	All the metal parts during punch process	Lubricate	Volatile Pressing Oil	100%
GOOBER OIL	All the metal parts during punch process	Lubricate	GOOBER OIL	100%
PAINT THINNER	Assembling Process	Assembling Assistance	Methyl Ethyl Ketone	10%-15%
			Butyle Acetate	5%-10%
			DDA	3%-5%
			N-Butyl Alcohol	25%-30%
			Acetic Ether	20%-30%
			Ethylene Glycol Monobutyl Ether	10%-15%
			Xylene	15%-20%