



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SNMPWEBCARD

For remote monitoring and control via SNMP, Web or Telnet

Highlights



- NEW firmware web-only version 12.06.0061 now available!
- Internal SNMP/Web management accessory card
- Provides remote monitoring and control of UPS systems and power conditions
- Network Time Protocol support for automatic updates to the card's real-time clock from an NTP server
- Compatible with any expansion slot-equipped Tripp Lite UPS System
- Simple installation and setup

Description

Tripp Lite's SNMPWEBCARD gives IT managers better visibility and control in high-density network environments. It enables any expansion slot-equipped Tripp Lite SmartPro or SmartOnline UPS System to be operated as a managed device on the network. The SNMPWEBCARD employs the SNMP network to remotely monitor and control UPS systems and site electrical conditions via a management platform or web browser. The SNMPWEBCARD can provide remote viewing of site electrical data, UPS status information and self-test logs. When used with Tripp Lite UPS systems equipped with load management receptacles, it can remotely reboot locked-up network devices without interrupting power to other critical loads. An optional ENVIROSENSE accessory module provides remote temperature/humidity monitoring and a dry contact interface to control and monitor alarm, security and telecom devices. The SNMPWEBCARD comes with a 2-year warranty. NEW firmware web-only version 12.06.0061 now available! - supports IPv6, Radius, and secure file transfer. Firmware is not applicable with cards running firmware version 12.04.0047 or earlier. NOTE: Existing 12.04.0048 and 12.04.0049 cards must be upgraded to the 12.04.0055 firmware prior to upgrading to 12.06.0061.

Applications

- Ideal for remote management and control of UPS and power data in LAN/WAN racks, computer rooms and data center environments

System Requirements

- Tripp Lite UPS/PDU with SNMPWEBCARD running Version 12.04.0055
- FTP utility
- Web browser
- Java Runtime Environment 1.6.026 or later
- NOTE: Existing 12.04.0048 and 12.04.0049 cards can be upgraded to the 12.04.0055 firmware to provide SNMPv3 support, then to 12.06.0061 for IPv6 support. Firmware is not applicable with cards running firmware version 12.04.0047 or earlier.

Package Includes

- SNMPWEBCARD
- Quick Start Installation Guide
- Configuration Cable
- Software CD including Owner's Manual & MIB files
- Cover Plates (secures card in UPS system's SNMP accessory slot)

Features

Enhanced UPS Management and Control: The SNMPWEBCARD makes any slot-equipped Tripp Lite UPS a managed device on the network, controllable via SNMP network management platforms or a web browser. This enables IT managers to remotely monitor current site electrical data, UPS self-test and alert logs, as well as logged power events such as blackouts, brownouts, overvoltages, and other electrical problems. When used with the customized load management receptacles available on select Tripp Lite UPS systems, the SNMPWEBCARD also support selective

rebooting of locked-up network equipment without disrupting power to other mission-critical loads.

Flexible Access: The SNMPWEBCARD features two-tier access, allowing both an administrator and a guest to log into the web browser to monitor or control the UPS system. Multiple user support allows viewing by a number of users simultaneously. Full Telnet access enables the UPS system to be remotely monitored and managed via a TELNET session. An optional SSL (Secure Socket Layer) security setting provides the capability to create an encrypted connection to the card via a web browser.

Advanced Network Management Tools: The SNMPWEBCARD can shut down remote operating systems via the network (supported operating systems must have Tripp Lite's Power Alert 12 installed). It can also provide alert notifications via email or SNMP traps, giving IT personnel the advantage of receiving an immediate event notification when a site electrical or UPS problem occurs. The SNMPWEBCARD provides real-time clock support to maintain the time of day and date even if the UPS is shut down. NTP (Network Time Protocol) support enables the card to receive automatic updates to its real-time clock from a NTP server.

Broad Compatibility: The SNMPWEBCARD supports multiple protocols supported including HTTP, HTTPS, PowerAlert Network Management System, SMTP, SNMPv1, SNMPv2, Telnet, SSH, FTP, DHCP, BOOTP. With 10/100 Mbps auto-sensing, the SNMPWEBCARD assures allows optimal communication compatibility with a current 10/100 Base-T network.

Specifications

OVERVIEW	
Model Type	Hardware
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
ENVIROSENSE	Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.)	1
WEXT3-SNMP	3-Year Extended Warranty - For All SNMP Products	1
WEXT5-SNMP	5-Year Extended Warranty - For All SNMP Products	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=3968.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.