
# LED MINI STAR

#### SCHEMATICS:

▶ Ultra thin 1/2" profile.

1/2"

No custom cords to buy or hide.



#### **DESCRIPTION:**

Ultra thin 3.5 watt LED under cabinet light fixture. Energy savings of 80% vs. Xenon/Halogen technology. Fixture circuitry allows expandable system design from 1 to 18 fixtures per remote power supply. 60,000-hour replaceable modules include CREE<sup>™</sup> LEDs at 2900K color temperature. Offered in single fixture and 3-light kits, and four fixture finishes.

# Z = FIXTURE TYPE

APPLICATIONS

Under cabinets

Display cases

Work stations

Cabinets

Shelves

Quick -

Connectors

F = Individual Fixture 3 = 3 Light Kit

#### **FEATURES** ▶ Ultra thin 1/2"

- fixture profile.
- Energy usage of only 3.5 watts per fixture.

3 light kit wiring schematic

24"

12″

Η

⊕ -**D** 

6.5"

36" Lead Wires

59"

- The same light output of Xenon/Halogen technology.
- ▶ 60,000-hour light source average life.
- ▶ CREE<sup>™</sup> LEDs inside.

**YY = FIXTURE FINISH** 

BK = Black

AL = Aluminum

WH = White

BZ = Bronze

- Pleasingly warm color temperature of 2900K.
- Single fixtures use standard CL2 lead wire to terminal block connectors.
- Available in four • fixture finishes: White, Bronze, Aluminum, Black

### **ORDERING LOGIC:**

LMS-Z-YY


#### SPECIFICATIONS:

Voltage	24VDC, Requires NSL LED Driver (18W, 60W, or 120W)	<b>M</b> .
Fixture Energy Rating	24VDC, 145mA, 3.5 watts	<b>U</b>
LED Color Temperature	2900K +/-200K	LISTED
Average LED Module Life	60,000 Hours	
Construction	Die cast aluminum base. Injection molded plastic covers. Frosted tempered glass lens.	
Cover Finish	White, Bronze, Aluminum, Black	
Base Finish	Aluminum	
Wiring Options	Individual fixtures can be mixed and matched up to 18 fixtures per driver (120W Driver).	
	Kits can be cord connected up to three fixtures per driver.	
Dimming	Not for use with dimmers.	
Packaging	Fixture in blister packs.	
Agency Approval	UL listed and labeled for all under-cabinet and in-cabinet applications. Damp Location.	



TYPE: **PROJECT:** NOTES:

## Single fixture wiring schematic



24"





72"

14 18W Driver

> Quick Connectors 3 Light Kit only

Switch