

**Switched Disconnects and Enclosures**  
**Unfused Hazardous Location Disconnect Switches**  
**30 Amp, 3 Pole**

# HUBBELL

## Features

- Copper-free aluminum construction with electrostatically applied polyester/epoxy finish to prevent corrosion
- Compact NEMA 4X enclosure and footprint allows easy installation in tight locations
- Gasketed flange with O-ring located inside bolt circle to seal out moisture
- Lockable handle to meet OSHA Lockout/Tagout regulations. Large visible rotary handle with "ON-OFF" indicator allows a quick means of disconnecting power
- Disconnects contain UL98 certified switch



## Ordering Information

Description	UPC Number	Catalog Number
30A 3-Pole Disconnect Switch with Auxiliary Contact	783585242620	HBLB7NFD13AA

## Online Resources

[eCatalog](#)  
[Installation Instructions](#)

## Specifications

Enclosure Material	Copper-free aluminum
Cover Bolts	316 Stainless Steel
O-Ring Gasket	Silicone
Finish	Grey Powder Polyester painted exterior, electrostatically applied

## Performance

Electrical	
Max. Working Voltage	600V AC
Mechanical	
Conduit Size	1 NPT
Terminal Wire Size	#14 AWG - #10 AWG

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

