



MILBANK
ENERGY AT WORK

S8930-XL



Catalog Number	S8930-XL
Marketing Product Description	7 Terminal Ringless Stud Heavy Duty Lever Bypass Overhead
UPC	784572273764
Length (IN)	13
Width (IN)	4.844
Height (IN)	19
Brand Name	Milbank
Type	Ringless Meter Socket
Application	Meter Socket
Standard	Non UL Listed;Type 3R
Voltage Rating	600 Volts Alternating Current
Amperage Rating	200 Continuous Ampere
Phase	3 Phase
Frequency Rating	60 Hertz
Size	13L x 4.844W x19H
Number Of Cutouts	0
Cutout Size	No Main Breaker
Cable Entry	Overhead and Underground and Side Wireway
Terminal	3/8 Inch Stud
Insulation	Glass Polyester
Mounting	Surface Mount

Enclosure G90 Galvanized Steel with Powder Coat Finish

Jaw Quantity 7 Terminal

Bypass Type Lever Bypass

Number of Meter Positions 1 Position

Equipment Ground Bonded Neutral

Hub Opening Small Closing Plate

Number Of Receptacles 0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.