



MILBANK
ENERGY AT WORK

SC6129-O



Catalog Number	SC6129-O
Marketing Product Description	13 Terminal Ringless Plain Top Pedestal With Test Switch Provision VT Pack Provision
UPC	784572692992
Length (IN)	4.125
Width (IN)	12
Height (IN)	84
Brand Name	Milbank
Type	Ringless Meter Socket
Application	Meter Socket
Standard	Non UL Listed;Type 3R
Voltage Rating	600 Volts Alternating Current
Amperage Rating	20 Continuous Ampere
Phase	3 Phase
Frequency Rating	60 Hertz
Size	4.125L x 12W x 84H
Number Of Cutouts	0
Cutout Size	No Main Breaker
Cable Entry	Underground
Terminal	Single Mechanical
Insulation	Glass Polyester
Mounting	Pedestal

Enclosure G90 Galvanized Steel with Powder Coat Finish

Jaw Quantity 13 Terminal

Bypass Type No Bypass

Number of Meter Positions 1 Position

Equipment Ground Ground Lug

Hub Opening Plain Top

Line Side Wire Range 12 - 10 AWG

Load Side Wire Range 12 - 10 AWG

Number Of Receptacles 0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.