

U2732-X-K7-CE



Catalog Number	U2732-X-K7-CE	Insulation	Glass Polyester
Marketing Product Description	7 Terminal Ringless Large Closing Plate Lever Bypass 2 Position Single Connector 4-6kcmil Consumers Energy 14-87123	Mounting	Surface Mount
UPC	784572461147	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Length (IN)	6	Jaw Quantity	7 Terminal
Width (IN)	32.125	Bypass Type	Lever Bypass
Height (IN)	25.25	Number of Meter Positions	2 Positions
Brand Name	Milbank	Equipment Ground	Ground Lug
Type	Ringless Meter Socket	Hub Opening	Large Closing Plate
Special Features	Consumers Energy	Line Side Wire Range	4 AWG - 600 kcmil or Two 1/0 AWG - 250 kcmil
Application	Meter Socket	Load Side Wire Range	2 AWG - 350 kcmil
Standard	UL Listed;Type 3R	Number Of Receptacles	0
Voltage Rating	600 Volts Alternating Current		
Amperage Rating	200 Continuous Ampere		
Phase	3 Phase		
Frequency Rating	60 Hertz		
Size	6L x 32.125W x 25.25H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Overhead or Underground with Center Wireway		
Terminal	Single Mechanical		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.