



MILBANK
ENERGY AT WORK

U5137-O-200S-10GR-CEC



Catalog Number	U5137-O-200S-10GR-CEC
Marketing Product Description	4 Terminal Ringless Plain Top 2-200 Ampere Main Breaker 520GR Double Pedestal Direct Bury Claiborne Electric Coop
UPC	784572494411
Length (IN)	15.8
Width (IN)	9.688
Height (IN)	80.063
Brand Name	Milbank
Type	Ringless Meter Socket
Special Features	Claiborne Electric Coop
Application	Mobile Home Power
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	200 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	15.8L x 9.688W x80.063H
Number Of Cutouts	1
Cutout Size	One 200 Ampere Main Breaker
Cable Entry	Underground

Terminal	Double Mechanical
Insulation	Glass Polyester
Mounting	Direct Bury
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	Horn Bypass
Number of Meter Positions	Double Power Head
Equipment Ground	Ground Bar
Hub Opening	No Hub Opening
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	1/0 AWG - 300 kcmil
Number Branch Circuits	8
Number Of Receptacles	1
Receptacle Configuration	One NEMA 5-20 Ground Fault

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.