



MILBANK
ENERGY AT WORK

U6134-RL-76GBGR



Catalog Number	U6134-RL-76GBGR
Marketing Product Description	5 Terminal Ringless Small Hub Open Lever Bypass 520GR 520GR 1450GB
UPC	784572696099
Length (IN)	4.844
Width (IN)	13
Height (IN)	35
Brand Name	Milbank
Type	Ringless Meter Socket
Special Features	Two Single Pole 20 Ampere Breakers and One Double Pole 50 Ampere Ground Fault Breaker
Application	Meter Socket
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	100 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	4.844L x 13W x35H
Number Of Cutouts	2
Cutout Size	Breaker Provision
Cable Entry	Overhead or Underground

Terminal	Lay in
Insulation	Glass Polyester
Mounting	Surface Mount
Enclosure	Aluminum with Powder Coat Finish
Jaw Quantity	5 Terminal
Bypass Type	Lever Bypass
Number of Meter Positions	1 Position
Equipment Ground	Ground Bar
Hub Opening	Small Hub Opening
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	6 AWG - 350 kcmil
Number Branch Circuits	6
Number Of Receptacles	3
Receptacle Configuration	One NEMA 14-50 and Two NEMA 5-20 Ground Fault

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.