



MILBANK
ENERGY AT WORK

U4554-X-Z21-K6SP-LI



Catalog Number	U4554-X-Z21-K6SP-LI
Marketing Product Description	13 Terminal Ringless Large Closing Plate Test Switch Prewired 21in-41in-10in Painted Steel Single Front Lift Off Cover Hasp Long Island Lighting Company
UPC	784572720817
Length (IN)	10
Width (IN)	21
Height (IN)	41
Brand Name	Milbank
Type	Ringless Meter Socket
Special Features	Long Island Lighting Company
Application	Meter Socket
Standard	UL Listed;Type 3R
Voltage Rating	600 Volts Alternating Current
Amperage Rating	320 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	10L x 21W x 41H
Number Of Cutouts	0
Cutout Size	No Main Breaker
Cable Entry	Overhead or Underground

Terminal	Single Mechanical
Insulation	Glass Polyester
Mounting	Surface Mount
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	6 Terminal
Bypass Type	No Bypass
Number of Meter Positions	1 Position
Equipment Ground	Ground Lug
Hub Opening	Large Closing Plate
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	4 AWG - 600 kcmil or Two 1/0 AWG - 250 kcmil
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.