




MILBANK
ENERGY AT WORK

U5168-XL-100-BL-NE



Catalog Number	U5168-XL-100-BL-NE
Marketing Product Description	4 Terminal Ringless Small Closing Plate Horn Bypass 1-100 Ampere Main Breaker 10 Circuit Loadcenter 9-16 In Barrel Lock With Bracket Provision
UPC	784572727489
Length (IN)	4.5
Width (IN)	14.125
Height (IN)	32.375
Brand Name	Milbank
Type	Ringless Meter Socket
Application	Meter Socket With Main And Load Center
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	200 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	4.5L x 14.125W x32.375H
Number Of Cutouts	1
Cutout Size	One 100 Ampere Main Breaker
Cable Entry	Underground

Terminal	Lay in
Insulation	Glass Polyester
Mounting	Surface Mount
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	No Bypass
Number of Meter Positions	1 Position
Equipment Ground	Ground Bar
Hub Opening	Small Closing Plate
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	6 AWG - 350 kcmil
Barrel Lock Provision	9/16 Inch Knockout and Angle Bracket for Barrel Lock Provision
Number Branch Circuits	8
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.