



**MILBANK**  
ENERGY AT WORK

## U5137-O-100S/200S



|                               |                                                                                                                |
|-------------------------------|----------------------------------------------------------------------------------------------------------------|
| Catalog Number                | U5137-O-100S/200S                                                                                              |
| Marketing Product Description | 4 Terminal Ringless Plain Top<br>Horn Bypass 1-100 1-200<br>Ampere Main Breaker Double<br>Pedestal Direct Bury |
| UPC                           | 784572752139                                                                                                   |
| Length (IN)                   | 16.063                                                                                                         |
| Width (IN)                    | 9.688                                                                                                          |
| Height (IN)                   | 80.063                                                                                                         |
| Brand Name                    | Milbank                                                                                                        |
| Type                          | Ringless Meter Socket                                                                                          |
| Application                   | Meter Socket With Main And<br>Load Center                                                                      |
| Standard                      | UL Listed;Type 3R                                                                                              |
| Voltage Rating                | Up to 240 Volts Alternating<br>Current                                                                         |
| Amperage Rating               | 200 Continuous Ampere                                                                                          |
| Phase                         | 1 Phase                                                                                                        |
| Frequency Rating              | 60 Hertz                                                                                                       |
| Size                          | 15.125L x 10W x 80H                                                                                            |
| Number Of Cutouts             | 2                                                                                                              |
| Cutout Size                   | One 200 Ampere Main<br>Breaker and One 100 Ampere<br>Main Breaker                                              |
| Cable Entry                   | Underground                                                                                                    |
| Terminal                      | Double Mechanical                                                                                              |

|                           |                                                 |
|---------------------------|-------------------------------------------------|
| Insulation                | Glass Polyester                                 |
| Mounting                  | Pedestal                                        |
| Enclosure                 | G90 Galvanized Steel with<br>Powder Coat Finish |
| Jaw Quantity              | 4 Terminal                                      |
| Bypass Type               | Horn Bypass                                     |
| Number of Meter Positions | Double Power Head                               |
| Equipment Ground          | 4 Barrel Ground Lug                             |
| Hub Opening               | Plain Top                                       |
| Line Side Wire Range      | 6 AWG - 350 kcmil                               |
| Load Side Wire Range      | 1/0 AWG - 300 kcmil                             |
| Number Of Receptacles     | 0                                               |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.