



MILBANK
ENERGY AT WORK

U6276-O-100S



Catalog Number	U6276-O-100S
Marketing Product Description	4 Terminal Ring Type Plain Top 1-100 Ampere Main Breaker 12 Circuit Load Center Single Pedestal Direct Bury Series Wired
UPC	784572777354
Length (IN)	7
Width (IN)	12
Height (IN)	76.375
Brand Name	Milbank
Type	Ring Type Meter Socket
Application	Mobile Home Power
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	200 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	4.563L x 12W x76.375H
Number Of Cutouts	1
Cutout Size	One 100 Ampere Main Breaker
Cable Entry	Underground
Terminal	Double Mechanical

Insulation	Glass Polyester
Mounting	Pedestal
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	No Bypass
Number of Meter Positions	1 Position
Equipment Ground	Ground Lug
Hub Opening	Plain Top
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.