

Single Pole Devices and Temporary Power  
Series 18 - 300A, 600V AC/250V DC

HUBBELL

Female Plug

Features

- Extra Long non-conductive inner sleeve
- Turn and Lock Symbol aids in the mating of devices
- Easily Identifiable Cable with cut off points for secure fit



Ordering Information

| Description                                            | Device Color | UPC Number  | Catalog Number |
|--------------------------------------------------------|--------------|-------------|----------------|
| 300A, thermoplastic elastomer, cable size #2 - 2/0 AWG | White        | 78358553936 | HBL18300FW     |

Listings

UL and cUL Listed  
UL Enclosure Types 3R, 4X, 12  
National Electric Code (NEC), ANSI/NFPA 70

Specifications

|                          |                         |
|--------------------------|-------------------------|
| Base Compound            | Thermoplastic Elastomer |
| Contact Material         | Brass                   |
| Retaining Screw Material | Nylon                   |

Performance

|                        |                                        |
|------------------------|----------------------------------------|
| <b>Electrical</b>      |                                        |
| Amperage Rating        | 300A Maximum                           |
| Voltage Ratings        | 600V AC Maximum; 250V DC Maximum       |
| <b>Mechanical</b>      |                                        |
| Product Identification | Ratings are a permanent part of device |
| Terminal Accommodation | #2 to 2/0 AWG                          |
| <b>Environmental</b>   |                                        |
| Flammability           | HB per UL94 or CSA 22.2. 0.17          |

Online Resources

eCatalog

