



MILBANK
ENERGY AT WORK

U8667-O-2/200



Catalog Number	U8667-O-2/200
Marketing Product Description	4 Terminal Ring Type Plain Top Double Pedestal 2-200 Ampere Main Breaker
UPC	784572291638
Length (IN)	12.593
Width (IN)	12
Height (IN)	52
Brand Name	Milbank
Type	Ring Type Meter Socket
Application	Meter Socket With Main
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	200 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	12.593L x 12W x52H
Number Of Cutouts	2
Cutout Size	Two 200 Ampere Main Breakers
Cable Entry	Underground
Terminal	Single Mechanical
Insulation	Glass Polyester

Mounting	Pedestal
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	No Bypass
Number of Meter Positions	2 Positions
Equipment Ground	Quadplex Ground
Hub Opening	Plain Top
Load Side Wire Range	1 AWG - 300 kcmil
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.