



MILBANK
ENERGY AT WORK

CP-PE-TYP5-2POS



Catalog Number	CP-PE-TYP5-2POS
Marketing Product Description	Photo Control Kit 1-HOA Switch 2 Position
UPC	784572179127
Length (IN)	2
Width (IN)	5
Height (IN)	6
Weight (LB)	1.5
Brand Name	Milbank
Type	PE Control Kit
Special Features	Male 4 Pin Connector
Application	Pedestal Accessory
Standard	UL Listed
Action	Provides 24/7 Control for Most Loads
Timing Range	24/7 Day
Contact Configuration	Normally Open
Contact Rating	24 Volts Alternating Current;120 Volts Alternating Current;240 Volts Alternating Current
Number Of Pins	4
Mounting	Internal Surface Mount
Number Of Poles	2
Phase	1 Phase

Connection	Hard Wired
Enclosure	No Enclosure
Size	4.75 Inches x 3.25 Inches x 3.25 Inches
Operating Temperature	Negative 20 Degrees Fahrenheit to 131 Degrees Fahrenheit

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.