Product data sheet
Characteristics

MPH22125
MTR MP DEVICE RINGLESS HORN 125A 2 POS.

Main

Commercial Status	Commercialised
Product or component type	Meter Center
Meter socket rated current	125 A
Main type	Main Lugs
Number of jaws	5
Number of meter sockets	2
Meter socket type	Ringless

Complementary

Main rated current	200 A
Bus rated current	200 A
Product certifications	UL listed
Range of product	Meter-Pak
Material	Aluminium busbar
Bypass type	Horn bypass
Enclosure material	Steel
NEMA degree of protection	NEMA 3R
[Ue] rated operational voltage	240 V AC
Product mounting	Surface
Network number of phases	1 phase
Service feed location	OH UG
AWG gauge	4...250 AWG/kcmil 1 copper 4...250 AWG/kcmil 1 aluminium
Wiring configuration	3-wire

Ordering and shipping details

Category	00021 - METER-PAK
Discount Schedule	DE4
GTIN	00785901208105
Nbr. of units in pkg.	1
Package weight(Lbs)	42.77
Returnability	Y
Country of origin	MX

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.