



Ring Terminal T&B Catalog Number:

UPC Number:
Status:
Description:

C26NPM
78621090648
Active

Non-Insulated Ring Terminal For Wire Range 12-10 Stud Size #10, Nickel-Plated, Metallic, Mylar Tape

WEB_USE

US Cutsheet PDF Catalog Link

<http://www-public.tnb.com/contractor/docs/stakon.pdf>

Features

These non-insulated ring terminals are made of electrolytic copper for high conductivity. They can be installed with crimping tools having a single indenter or double indenter (recommended for solid wire). Serrated barrel increases grip on wire.

Application

Wiring terminations for wiring harness, panelboard, telecommunications, and automotive.

General

Insulation Type	Non-Insulated
Terminal Series	C
Material	Copper
Finish	Nickel Plated
Color	Metallic
Wire Range	12-10
Stud Size	#10

Dimension Information

Stock Thickness	.04
A (inches)	.85
B (inches)	.38
C (inches)	.27
M (inches)	.66

Specifications

Temperature Rating	150°C
Voltage Rating	600V
Flammability Rating	UL 94 V-0

Tooling

Tool Charts	Available on Website
Application Tools	WT110M, WT111M, WT112M, WT2000, ERG4002
Recommended Tool	12050

Packaging

T&B Order Multiple	1000
T&B Inner Pack	1000
Package in Units	5000
Package Type	Mylar Tape
T&B Sold in UOM	Each
T&B Weight Per UOM	3.13 lbs. per 1000

Application Support

Overview	Available on Website
Wire Guide Tables	Available on Website

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications



File Nbr:
E9809

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com