



Open Switches T&B Catalog Number:

UPC Number: OT80F3
Status: 80432541565
Description: Active

3 pole, 80 amps rated at 600 VAC, UL 508, open non-fusible disconnect switch

Features

- Quick make, quick brake mechanism
- Extremely compact size
- Finger-proof construction with no hazardous exposed parts

Application

- Suitable for use as motor disconnects or industrial control panel disconnects on service entrance equipment, panelboards, switchboards, industrial control equipment, motor control centers, etc.
- Motor feeder applications and motor feeder short circuit and ground fault protection

General

Number of Poles: 3
Series: Non-fusible

Approvals

UL Class: UL 98

Specifications

Rated Current (Amps): 80
Rated Voltage AC: 600

Packaging

T&B Inner Pack: 1
Package in Units: 10
T&B Sold in UOM: Each
T&B Weight Per UOM: 0.59 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com