



**Distribution Compression Splice**

**T&B Catalog Number:**

AC20

**UPC Number:**

78378605104

**Status:**

Active

**Description:**

Aluminum 9 1/4 inch Full-Tension Distribution Compression Splice for Wire Range: 2/0 (7, 19), Mechanical Dies: BY33, C-167, W-247, 737, Hydraulic Dies: B39EA, 247, 737, 747

**Features**

- Center stop ensures proper conductor positioning.
- External end taper provides conductor stress relief, ease of stringing and corona protection.
- Internal end chamfer enables easy conductor insertion and prevents sharp edge contact with conductor.
- Standards compliant. Meets ANSI C119.4 requirements - withstands 95 percent of conductor rated breaking strength.

**General**

Style	Full-Tension
Material	Aluminum
Wire Size	2/0 (7, 19)
EEL Classification	10A

**Dimension Information**

Length (inches)	9 1/4
-----------------	-------

**Tooling**

Mechanical Tool OD58 Dies	BY33
Mechanical Tool OD58 Crimps Per End	16
Mechanical Tool MD Series Dies	C-167, W-247
Mechanical Tool MD Series Crimps Per End	16, 8
Mechanical Tool O-52 Dies	737
Mechanical Tool O-52 Crimps Per End	16
Hydraulic Tool JB12B Dies	B39EA
Hydraulic Tool JB12B Crimps Per End	4
Hydraulic Tool Y Series Dies	247
Hydraulic Tool Y Series Crimps Per End	4
Hydraulic Tool WH Series Dies	737, 747
Hydraulic Tool WH Series Crimps Per End	8, 4
End	

**Packaging**

Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	28 lbs. per 100

**Notes**

OD58 Dies are interchangeable with those listed for O-52.

**Certifications**

RoHS Compliance	Yes
-----------------	-----

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)