



**Distribution Compression Splice**

**T&B Catalog Number:**

AC2-TB

**UPC Number:**

78378605102

**Status:**

Active

**Description:**

Aluminum 4 1/8 inch Full-Tension Distribution Compression Splice for Wire Range: 4(7), Mechanical Dies: BY23, W-163, 1/2, Hydraulic Dies: B17EA, 163, 1/2, 510

**Features**

- Center stop ensures proper conductor positioning.
- External end taper provides conductor stress relief, ease of stringing and corona protection.
- Internal end chamfer enables easy conductor insertion and prevents sharp edge contact with conductor.
- Standards compliant. Meets ANSI C119.4 requirements - withstands 95 percent of conductor rated breaking strength.

**General**

Style	Full-Tension
Material	Aluminum
Wire Size	4(7)
EEL Classification	6A

**Dimension Information**

Length (inches)	4 1/8
-----------------	-------

**Tooling**

Mechanical Tool OD58 Dies	BY23
Mechanical Tool OD58 Crimps Per End	6
Mechanical Tool MD Series Dies	W-163
Mechanical Tool MD Series Crimps Per End	6
Mechanical Tool O-52 Dies	1/2
Mechanical Tool O-52 Crimps Per End	6
Hydraulic Tool JB12B Dies	B17EA
Hydraulic Tool JB12B Crimps Per End	2
Hydraulic Tool Y Series Dies	163
Hydraulic Tool Y Series Crimps Per End	2
Hydraulic Tool WH Series Dies	1/2, 510
Hydraulic Tool WH Series Crimps Per End	4

**Packaging**

T&B Inner Pack	25
Package in Units	250
T&B Sold in UOM	Each
T&B Weight Per UOM	6.55 lbs. per 100

**Notes**

OD58 Dies are interchangeable with those listed for O-52.

**Certifications**

RoHS Compliance	Yes
-----------------	-----

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)