High Temperature Liquidtight System

T&B Catalog Number: ATX250-TB
UPC Number: 78621091743
Status: Active
Description:

2-1/2 in. black thermoplastic rubber liquidtight flexible conduit, inside radius bend-8.0 in.

Features

	Construction utilizes the flexibility of a standard core, coupled with the advantage of a thermoplastic rubber jacket that is virtually unaffected by temperature extremes and contains no halogens.
	Flammability rating of UL 94-HB.

Application

	Used in applications where concerns of resistance to temperature exposure exist to include heavy outdoor equipment, boilers and furnaces, pulp and paper mills and sub-zero areas.

General

Material	Thermoplastic Rubber
Color	Black
Inside Bend Radius (inches)	8

Dimension Information

Length (feet)	25
Size (inches)	2 1/2
Inside Bend Radius (inches)	8

Packaging

T&B Order Multiple	25
Package in Units	25
T&B Sold in UOM	Feet
T&B Weight Per UOM	188 lbs. per 100

Application Support

Product Overview	Available on Website

Certifications

RoHS Compliance	Yes

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com