



Deltec Kit
T&B Catalog Number:

CSS-10K
 78621070749
 Active

UPC Number:
Status:
Description:

Cable Tie Deltec Kit, 500 ft. reel, 300 Heads

Features

Perfect for coaxial, fiber optic and all other communication and electrical conducting cables.

Strap and body are weatherable acetal, offering superior resistance to sunlight, moisture and salt environments.

Locking device is marine-grade corrosion-resistant copper alloy.

Application

Ideal solution for bundling in harsh outdoor environments.

General

Material Weather-Resistant Acetel
 Color Black

Specifications

Temperature Rating -30°F to 150°F

Tooling

Application Tools WT3D

Packaging

Package in Units 1
 T&B Sold in UOM Each
 T&B Weight Per UOM 1240 lbs. per 100

Notes

The recommended maximum continuous static loading for the Deltec® straps is 20 lbs. Per strap. For best results suggested spacing is 15 inches. It is the responsibility of the user to determine whether or not their application meets our recommendation.

Certifications

RoHS Compliance Yes

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com