



**Cable Spacers**  
**T&B Catalog Number:**

CSS-360  
 78621056804  
 Active

**UPC Number:**  
**Status:**  
**Description:**

Cable Tie Deltec Modular Spacers for Coaxial Cable

**Features**

Perfect for coaxial, fiber optic and all other communication and electrical conducting cables.

Strap and body are weatherable acetal, offering superior resistance to sunlight, moisture and salt environments.

Locking device is marine-grade corrosion-resistant copper alloy.

**Application**

Ideal solution for bundling in harsh outdoor environments.

**General**

Material Weather-Resistant Polypropylene  
 Color Black

**Specifications**

Temperature Rating -30°F to 150°F

**Tooling**

Application Tools WT3D

**Packaging**

T&B Order Multiple 250  
 Package in Units 500  
 Package Type Bulk  
 T&B Sold in UOM Each  
 T&B Weight Per UOM 13.1 lbs. per 1000

**Notes**

The recommended maximum continuous static loading for the Deltec® straps is 20 lbs. Per strap. For best results suggested spacing is 15 inches. It is the responsibility of the user to determine whether or not their application meets our recommendation.

**Certifications**

RoHS Compliance Yes

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email:techsupport@tnb.com