



Blackburn®

AMT Connectors
T&B Catalog Number:

UPC Number:
Status:
Description:

AMTD50063
 78378625944
 Active

AMT 3 Port Both Sides PVC Connector for Wire Range 500MCM-6 Str.

Features

PVC Insulation eliminates insulation failures and reduces outage costs. Removable port and screw plugs.

Compact design provides space efficiencies.

All cable entry are equipped with an anti-oxidation compound.



General

Style	Both Sides
Insulation	PVC
Material	Aluminum
Wire Range	500MCM-6 Str.
Number of Ports	3
Hex Size	3/8

Dimension Information

Length (inches)	4.12
Width (inches)	2.63
Height (inches)	3.04

Specifications

Temperature Rating	90°C
Voltage Rating	600V

Packaging

Package in Units	10
T&B Sold in UOM	Each
T&B Weight Per UOM	1 lbs. Each

Certifications



File Nbr:
 E9809

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com