



Blackburn®

AMT Connectors

T&B Catalog Number:

UPC Number:

Status:

Description:

AMTTC4

78378625919

Active

AMT 2 Port Splice Offset PVC Connector for Wire Range 4-14 Str.

Features

PVC Insulation eliminates insulation failures and reduces outage costs. Removable port and screw plugs.

Compact design provides space efficiencies.

All cable entry are equipped with an anti-oxidation compound.

General

Style	Splice Offset
Insulation	PVC
Material	Aluminum
Wire Range	4-14 Str.
Number of Ports	2
Hex Size	1/8

Dimension Information

Length (inches)	1.24
Width (inches)	1.25
Height (inches)	1.42

Specifications

Temperature Rating	90°C
Voltage Rating	600V

Packaging

Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	0.25 lbs. Each

Notes

UL listed and CSA certified for 600 volts, 90 degrees Celcius.

Certifications



File Nbr:

E9809

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com