

HBE11-IUB



Brand Features

The 0-10V Dimming Fixture Mount PIR Indoor/Outdoor Wet Location Occupancy Sensor is specifically designed to be mounted directly to an industrial fluorescent fixture or electrical junction box for control of 0-10V dimmable fixtures. The sensor is IP65 rated making it ideal for wash down applications in indoor and outdoor locations.

Item Description

Dimming PIR Occupancy Sensor, Fixture Mount, 120/277/347VAC, IP65 Rating for Low-Temp, Water Tight, Indoor/Outdoor, Adjustable time delay between 1m-15m, Downward and upward facing daylight sensor (selectable via dipswitch), Dimming Presets Unoccupied: 70%, 60%, 50% & 20%, UL and cUL Listed. Lens Sold Separately. Color: White.

Features and Benefits

- Controls 0-10V dimmable ballasts for daylight harvesting applications
- Interchangeable high/low area detection lenses in 360° view or aisle patterns*
- Full OFF timer delay
- 8-second test mode with 1, 5, 10 and 15 minute time outs
- Unoccupied dimming presets: 70%, 60%, 50%, 20%
- IP65 rated
- Meets energy code requirements for ASHRAE 90.1, California Title 24 and IECC, UL and cUL listed

*Lenses must be ordered separately

Color: White

UPC Code: 07847770585

Country Of Origin: China

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

