


Mini-Com® Shielded High-Density Modular Patch Panels

specifications

Shielded 48-port high-density patch panels shall occupy a single rack space, and be made of a stainless steel panel with molded rear snap-in faceplates that include a metal bonding strip that runs through the front midsection of the faceplate. Shall accept all Mini-Com® shielded jack modules for shielded installations and shall mount to standard 19" racks or cabinets. Patch panel shall be available in 48 ports in one rack space in both flat and angled designs. Shielded 48-port high-density patch panels shall be easily identified with pre-numbered ports.



technical information

Mounting option:	Mounts to standard EIA 19" rack or cabinets; mounts to 23" rack with optional extender brackets (PEB1)
Packaging:	Packaged with pre-installed snap-in faceplates with preassembled metal bonding strip. Includes mounting hardware: standard #12-24 and M6 (4 each); and grounding screws: #12-24 and M6 (2 each)
Material:	Panel manufactured from stainless steel; faceplate is ABS plastic; bonding strip is PHOS bronze

key features and benefits

Modular	Accepts all Panduit® Mini-Com® shielded modules
High density	More modules per rack space: 48 ports per 1 RU
Identification	Pre-numbered ports
Angled design	Allows cable to flow to each side of the rack and minimizes the need for horizontal cable managers
Optional strain relief bars	A variety of styles available to help manage and route cable
Optional angled filler panels	Reserve space for future use and promote proper airflow and cooling

applications

Mini-Com® 48-port high-density patch panels are an ideal solution in areas where rack or cabinet space is an issue.

The angled version increases rack density and reduces the need for horizontal cable management systems, managing high-density network applications in one-fourth the area needed for conventional cable management systems. A strain relief bar is recommended to properly support and route the rear cables.

Mini-Com® Modules can be easily switched or replaced as required. Blank modules will reserve space for future use or growth. Most panels are typically used in a telecommunication closet or cabinet but will work in other areas as well.

When installing the patch panel on the rack, the use of patented thread-forming bonding screws bond the shielded panel to the rack. The combination of shielded patch panels, shielded jack modules, and accessories provide a properly grounded system.

Mini-Com® Shielded High-Density Modular Patch Panels

Flat:	CP48HDBL
Angled:	CPA48HDBL

Mini-Com® Shielded Jack Modules

Category 6A:	CJS6X88TGY
Category 6:	CJS688TGY
Category 5e:	CJS5E88TGY

Shielded Patch Cords

TX6A, foot lengths:	STP6X*IG*
TX6A, meter lengths:	STP6X*MIG*
TX5e, meter lengths:	STPCH*MBBL*

Angled Filler Panels and Covers

1RU:	CPAF1BLY
2RU:	CPAF2BLY
Transitional Cover:	CPATCBL

Strain Relief Bars and Accessories

With integrated tie mounts:	SRBM19BLY
7" offset multi-depth:	SRB19MDBL
7" offset (inward mounting**):	SRBD7BL
With cable tie mounts:	SRBCT
Strain relief bar brackets:	SRBBRKT

Replacement Bonding Screws

#12-24 English:	RGTBS-C
M6 metric:	RGTBSM6-C

Replacement Thread-Forming Kits

#12-24 English:	RGTBSG
M6 metric:	RGTBSM6G


*For standard color and length options, please visit www.panduit.com.

**Bars with inward mounting feature require 19.75" clearance between rails or cabinet walls.

Mini-Com[®] Shielded High-Density Modular Patch Panels

Label Chart

Part Number	Label Type	Laser/Ink	LS8	Thermal
CP48HDBL	Adhesive	—	T024X000VPC-BK	T024X000FJT
CPA48HDBL	Adhesive			



Dimensions are in inches. (Dimensions in parenthesis are metric).

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA
Markham, Ontario
cs-cdn@panduit.com
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
cs-emea@panduit.com
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
cs-ap@panduit.com
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
cs-japan@panduit.com
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA
Guadalajara, Mexico
cs-la@panduit.com
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
cs-aus@panduit.com
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

For more information

Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com
or by phone: 800.777.3300

PANDUIT[®]

©2016 Panduit Corp.
ALL RIGHTS RESERVED.
COSP299--WW-ENG
8/22/2016