

# TX6A-SD™ 10Gig™ UTP Patch Cords with MaTriX Technology

## specifications

Category 6A/Class E<sub>A</sub>, UTP patch cords shall be constructed of 26 AWG stranded copper cable with an enhanced performance modular plug on each end. Copper conductors in patch cable shall be twisted in pairs and separated by a quadrant separator. All four pairs shall be surrounded by matrix tape and a flame retardant jacket. The patent pending matrix tape shall suppress alien crosstalk and allow 10 Gb/s transmission. Patch cord cable shall be offered in multiple colors and lengths for design flexibility with a strain relief boot on each modular plug. All patch cords shall be compatible with both T568A and T568B wiring schemes.



## technical information


### Category 6A/Class E<sub>A</sub> channel performance:

Certified channel performance in a 4-conductor configuration up to 70 meters and exceeds the electrical and alien crosstalk performance requirements of ANSI/TIA-568-C.2 Category 6A and ISO 11801 Class E<sub>A</sub> standards for supporting 10GBASE-T transmission over twisted-pair cabling systems as part of the Panduit TX6A-SD™ 10Gig™ UTP Copper Cabling System with MaTriX Technology

\*Note: The cable utilizes 26 AWG conductors which does not meet the 24 to 22 AWG conductor size of horizontal cable in ANSI/TIA-568-C.2.5.3, resulting in increased attenuation which de-rates the maximum channel distance to 70 meters (229 feet)

<b>Cable diameter:</b>	0.240 in. (6.1mm) nominal
<b>FCC and ANSI compliance:</b>	Meets all applicable ANSI/TIA-968-A; contacts are plated with 50 microinches of gold for superior performance
<b>IEC compliance:</b>	Meets IEC 60603-7
<b>RoHS compliance:</b>	Compliant
<b>PoE compliance:</b>	Meet requirements of IEEE 802.3af and IEEE 802.3at for PoE applications
<b>UL rated:</b>	UL 1863 approved
<b>Flammability rating:</b>	CM or LSZH

## key features and benefits

<b>Interoperable</b>	Compatible with components of the TX6A™ 10Gig™ UTP Copper Cabling System with MaTriX Technology (100 meter solution) for increased design flexibility
<b>MaTriX Technology</b> 	Provides superior suppression of both PSANEXT and PSAACR-F; improves the installation flexibility by allowing cable combing in existing pathways without compromising performance
<b>Smaller cable diameter than most Category 6 patch cords and flexible cable design</b>	Improved cable routing and management in high density applications enabling easier installations
<b>100% performance tested</b>	Confidence that each patch cord delivers specified performance
<b>Superior headroom warranty</b>	Provides the highest margins above the industry standard for both electrical and alien crosstalk performance
<b>Center de-embedded plug</b>	Performs in center of ANSI/TIA-568-C.2 component range ensuring interoperability and superior performance
<b>Integral pair manager</b>	Optimizes performance, consistency, and reliability by reducing untwist at plug
<b>Patented tangle-free latch</b>	Prevents snags and provides easy release, saving time and providing reliability on frequent moves, adds, and changes
<b>Slender strain relief boot</b>	Provides easy access in high-density applications
<b>Robust construction</b>	Rated to 2500 mating cycles
<b>Identification</b>	Provides identification of performance level, length, and quality control number for future traceability
<b>Variety of cable colors and lengths</b>	Meets individual length and color-coding requirements for greater system flexibility
<b>Color bands (optional)</b>	Snap onto cable, allowing additional color-coding options
<b>RJ45 plug lock-in device (optional)</b>	Secures plug into jack to prevent unauthorized removal of patch cord

## applications

The TX6A-SD™ 10Gig™ UTP Copper Cable is a component of the TX6A-SD™ 10Gig™ Copper Cabling System with MaTriX Technology. Interoperable and backward compatible, this end-to-end system provides design flexibility to protect network investments well into the future. Key applications include:

- 10GBASE-T Ethernet
- Data center I/O consolidation
- Data center server virtualization
- Back-bone aggregation
- Parallel processing and high speed computing

**www.panduit.com**

# PANDUIT®

## SPECIFICATION SHEET

### TX6A-SD™ 10Gig™ UTP Copper Cabling System with MaTriX Technology

#### TX6A-SD™ 10Gig™ UTP Patch Cords with MaTriX Technology

**CM (foot lengths):** UTP6ASD^BU  
**CM (meter lengths):** UTP6ASD^MBU  
**LSZH (meter lengths):** UTP6ASDL^MBU

#### Mini-Com® TX6A™ 10Gig™ UTP Jack Module with MaTriX Split Foil Technology

**Jack module:** CJ6X88TG\*  
**Shuttered jack module:** CJD6X88TG\*

#### TX6A-SD™ 10Gig™ UTP Copper Cable with MaTriX Technology (70 meter solution)

**Plenum:** PUP6ASD04\*-UG  
**Riser:** PUR6ASD04\*-CG<sup>1</sup>  
**LSZH:** PUL6ASD04\*\*~EG  
**CM:** PUC6ASD04\*\*~EG

#### TX6A™ 10Gig™ UTP Copper Cable with MaTriX Technology (100 meter solution)

**Plenum:** PUP6A04\*-UG  
**Riser:** PUR6A04\*-UG<sup>2</sup>  
**LSZH (60332-1):** PUL6A04\*\*~^G  
**LSZH (60332-3):** PUZ6A04\*\*~EG  
**CM:** PUC6A04\*\*~EG

#### Mini-Com® Angled Modular Patch Panels

**24-port, 1 RU:** CPPA24FMWBLY  
**48-port, 2 RU:** CPPA48FMWBLY  
**72-port, 2 RU:** CPPLA72WBLY

#### Mini-Com® Flat Modular Patch Panels

**24-port, 1 RU:** CPP24FMWBLY  
**48-port, 1 RU:** CPP48HDWBLY  
**48-port, 2 RU:** CPP48FMWBLY  
**72-port, 2 RU:** CPP72FMWBLY

For additional modular patch panels reference [www.panduit.com](http://www.panduit.com)

#### Tools and Accessories

**Patch cord removal tool:** PCRT1  
**Flashlight kit:** KPCRT1-FL  
**Patch cord color band:** PCBAND\*\*\*-Q  
**Standard RJ45 plug lock-in device:** PSL-DCPLX‡  
**Recessed RJ45 plug lock-in device:** PSL-DCPLRX‡

<sup>^</sup>For lengths 3 to 20 feet (increments of one foot) 20, 25, 30, 35, or 40 feet change the length designation in part number to the desired length. For standard cable colors other than Off White, add suffix BL (Black), BU (Blue), GR (Green), RD (Red), YL (Yellow), OR (Orange), or VL (Violet) at the end of the part number. LSZH available in Off White and BU (Blue) only. For example, the part number for a blue, 15-foot patch cord is UTP6ASD15BU.

<sup>^^</sup>For lengths 1, 2, 2.5, 3, 5 meters, change the length designation in the part number to the desired length. For standard cable colors other than Off White, add suffix BL (Black), BU (Blue), RD (Red), YL (Yellow), GR (Green), OR (Orange), or VL (Violet). LSZH patch cable available in Off White or BU (Blue). For example, the part number for a blue, 5-meter patch cord is UTP6ASD5MBU.

<sup>\*</sup>To designate color, add suffix IW (Off White), EI (Electric Ivory), AW (Arctic White), WH (White), IG (International Gray), OR (Orange), RD (Red), BU (Blue), GR (Green), YL (Yellow), or VL (Violet).  
<sup>\*\*</sup>To designate color, add suffix BU (Blue), WH (White), YL (Yellow), or IG (International Gray).

<sup>1</sup>Substitute PUR6ASD04\*-UG for alternative manufacturing location.


<sup>2</sup>Substitute PUR6A04\*-CG for alternative manufacturing location.

<sup>\*\*\*</sup>To designate color, add suffix BU (Blue) or WH (White). For additional cable colors, contact customer service.

<sup>†</sup>To designate color, add suffix WH (White), EI (Electric Ivory), IG (Int'l Gray), BL (Black), BU (Blue), RD (Red), YL (Yellow), GR (Green), OR (Orange), or VL (Violet) before -Q in part number. 25/package.

<sup>‡</sup>For colors other than Red, add -BL (Black), -BU (Blue), -GR (Green), -YL (Yellow), -OR (Orange), -IW (International White), or -IG (International Gray) to the end of the part number. 10/package. Add -C for bulk packages of 100. Contact customer service for keyed connectivity, bulk packaged jack modules and patch cords.

# TX6A-SD™ 10Gig™ UTP Patch Cords with MaTriX Technology



T568B Wiring Scheme

Plug Position	Cable Wire
1	White/Orange
2	Orange
3	White/Green
4	Blue
5	White/Blue
6	Green
7	White/Brown
8	Brown

## WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA  
Markham, Ontario  
cs-cdn@panduit.com  
Phone: 800.777.3300

PANDUIT EUROPE LTD.  
London, UK  
cs-emea@panduit.com  
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.  
Republic of Singapore  
cs-ap@panduit.com  
Phone: 65.6305.7575

PANDUIT JAPAN  
Tokyo, Japan  
cs-japan@panduit.com  
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA  
Guadalajara, Mexico  
cs-la@panduit.com  
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.  
Victoria, Australia  
cs-aus@panduit.com  
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to [www.panduit.com/warranty](http://www.panduit.com/warranty)

For more information

Visit us at [www.panduit.com](http://www.panduit.com)

Contact Customer Service by email: [cs@panduit.com](mailto:cs@panduit.com)  
or by phone: 800.777.3300 and reference COSP194

**PANDUIT®**

©2011 Panduit Corp.  
ALL RIGHTS RESERVED.  
Printed in the U.S.A.  
**SA-COSP194**  
Replaces SA-COSP174  
5/2011