



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

KPA8CTP  
 7818100355599  
 SCRULUG,#14 Sol-#6 Str  
 Active

**Web Use**  
 BURNDY Product Line

Dimensional	
Length (in)	1.04
Thickness (in)	4/57
Height (in)	0.81
Stud Size (in)	#10
Thickness	0.07
D - in	0.56
Pad Width (in)	0.38
N (in)	0.22
Strip Length	15/32
General	
Number of Holes	1
Number of Screws	1
Product Description	Copper Alloy Scrulug, 14 Sol. - 8 Str., .95 in L, .38 in W, Tin Plated
Conductor(s)	
Copper Solid Size (Range)	14 AWG-6 AWG
Copper Stranded (Range)	14 AWG-6 AWG
Physical	
Screw Type	Slot
Type of Hardware	1/4 Dia.Slot Robertson
Installation Torque	35
Type of Plating	Tin
Connector Type	Terminal
Plated (Yes or No)	Y
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175