



BURNDY Catalog Number YA362NFXB
UPC Number 7818100399466
Description BELLED CULUG-450FLEX-NEM
Status Active

Web Use
 BURNDY Product Line

Dimensional	
Tongue Angle	Straight
Length (in)	6.84
Tongue Type	Standard
Barrell Style	Belled
Bolt Hole Size (in)	0.52
Barrel Type	Long
Thickness	0.26
B Length (in)	2.95
Pad Width (in)	1.73
E - in	1.75
Strip Length	3-1/16
General	
Number of Holes	2
Product Description	Cu Comp Terminal Flex Cond(Telecom), 2 Hole/W/O/InspWindow, 444.4 kcmil(1100/#24)DLO, 600 V-35 kV, 1/2" Stud, 1.75" Spacing, Lng bbl, Belled End
Conductor(s)	
Aircraft Cable Size (Range)	N/A
Flex (Class H) Size - Range	444.4
Flex (Class I) Size - Range	444.4
Copper Solid Size (Range)	N/A
DLO Size (Range)	444.4 (1100/#24)
Navy Cable Size (Range)	N/A
Copper Stranded (Range)	N/A
Flex (Class G) Size - Range	444.4
Flex (Class M) Size - Range	444.4
Physical	
Type of Plating	Tin
Bolt Hole Size	1/2
Color Code	Brown
Plated (Yes or No)	Y
Index Number	20
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA
 47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services
 47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175